

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
State - E-1027	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
TEXACO Inc.		State of N. M. "CZ"
3. Address of Operator		9. Well No.
P. O. Box 728 - Hobbs, New Mexico		1
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER J, 1945 FEET FROM THE South LINE AND 1945 FEET FROM		Ranger Lake (Penn)
THE East LINE, SECTION 14 TOWNSHIP 12-S RANGE 34-E NMPM.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
4156' (GR)		Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Total Depth - 358'
Spudded 15" Hole at 2:30 P. M. May 17, 1965

Ran 344' of 11 3/4" O. D. Casing, 23.72 LB, Spiral Weld, NEW, and cemented at 358' with 300 Sx. Class "C" neat with 2% CACL. Plug at 328'. Cement Circulated. Temperature of mixing slurry - 72°. Strength 12 Hours - 1600 P. S. I. Bottom Hole Temperature - 64°. Job complete 1:30 A. M. May 18, 1965.

Tested 11 3/4" O. D. Casing for 30 minutes with 600 P. S. I. from 12:30 P. M. to 1:00 P. M. May 18, 1965. Tested O. K. Drilled cement plug and re-tested for 30 minutes with 600 P. S. I. from 1:30 P. M. to 2:00 P. M. May 18, 1965. Tested O. K. Job complete 2:00 P. M. May 18, 1965.

NOTE: This form reflects a change in the Casing program as shown on the Form C-101, Approved by the New Mexico Oil Conservation Commission May 10, 1965. Surface casing program changed from 10 3/4" Casing to 11 3/4" Casing, 23.72 pound, Spiral Weld.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>H. D. Raymond</u>	TITLE <u>Assistant District Superintendent</u>	DATE <u>May 19, 1965</u>
APPROVED BY <u>[Signature]</u>	TITLE <u></u>	DATE <u></u>
CONDITIONS OF APPROVAL, IF ANY:		