DISTRIBUTION SANTA FE FILE U.S.G.S. DISTRIBUTION NEW MEXICO OIL CONSERVATION COMMISSION	PS Of Form C-103 Supersedes Old
FILE NEW MEXICO OIL CONSERVATION COMMISSION	
	Supersedes Old C-162 Old C-103
U.S.G.S.	Effective 9-105
	28 pt
LAND OFFICE	5a. Indicate tone of Lease
OPERATOR	State Fee Fee
	5. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS	0G-801
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. 1. 1.	
OIL WELL OTHER-	7. Unit Agreement Name
2. Name of Operator	
Texas Pacific Oil Company	8. Farm or Lease Nume
3. Address of Operator	State "AH"
P.O. Box 1069 - Hobbs, New Mexico	9. Well No.
4. Location of Well	1
UNIT LETTER F 1980	10. Field and Pool, or Wildcat
UNIT LETTER F 1980 FEET FROM THE North LINE AND 1980 FEET FRO	N. Ranger Lake
THE West LINE, SECTION 14 TOWNSHIP 12 RANGE 34 NMPM	
LINE, SECTION 44 TOWNSHIP 12 RANGE 34 NMPM	MIHHHHHH
15. Elevation (Show whether DF, RT, GR, etc.)	
4152.6 GL	12. County
Check Appropriate Pour To L. 12	Les
Check Appropriate Box To Indicate Nature of Notice, Report or Ot	her Data
SUBSEQUEN	T REPORT OF:
PERFORM REMEDIAL WORK	
TEMPORARILY ABANDON PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
PULL OR ALTER CASING	PLUG AND ABANDONMENT
CHANGE PLANS CASING TEST AND CEMENT JOB X	
OTHER	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.	
1. Ran 128 Jts. (4165) 8-5/8" 32# & 24#, H-40 & J-55 ST&C Casing.	
Table Casing.	Set at 4177'.
2. Cemented w/1215 Ske Theory W/cel C-3 3037	/- / -
There one is a first the state of the state	W/1% D-30 in 325 sks.
incor; 200 sks Incor w/2% Gel. Total 2630 sks.	2 2-7
Total Loyo Okas.	
2002 2000 543.	
3. Pumped plug down to 4112 at 11:00 PM. Cement did not circulate.	
3. Pumped plug down to 4112 at 11:00 PM. Cement did not circulate.	
3. Pumped plug down to 4112 at 11:00 PM. Cement did not circulate. 4. Ran Temperature survey. T.O.C940.	•
3. Pumped plug down to 4112 at 11:00 PM. Cement did not circulate. 4. Ran Temperature survey. T.O.C940.	•
 Pumped plug down to 4112 at 11:00 PM. Cement did not circulate. Ran Temperature survey. T.O.C940. Ran 200 1" pipe outside 8-5/8" casing. Cemented w/150 sks. reg. 	•
 Pumped plug down to 4112 at 11:00 PM. Cement did not circulate. Ran Temperature survey. T.O.C940. Ran 200 1" pipe outside 8-5/8" casing. Cemented w/150 sks. reg. 	•
3. Pumped plug down to 4112' at 11:00 PM. Cement did not circulate. 4. Ran Temperature survey. T.O.C940'. 5. Ran 200' 1" pipe outside 8-5/8" casing. Cemented w/150 sks. reg. 6. W.O.C. 32 Hrs. Tested casing w/1000# for 30 minutes.	•
3. Pumped plug down to 4112' at 11:00 PM. Cement did not circulate. 4. Ran Temperature survey. T.O.C940'. 5. Ran 200' 1" pipe outside 8-5/8" casing. Cemented w/150 sks. reg. 6. W.O.C. 32 Hrs. Tested casing w/1000# for 30 minutes.	•
3. Pumped plug down to 4112' at 11:00 PM. Cement did not circulate. 4. Ran Temperature survey. T.O.C940'. 5. Ran 200' 1" pipe outside 8-5/8" casing. Cemented w/150 sks. reg. 6. W.O.C. 32 Hrs. Tested casing w/1000# for 30 minutes.	•
3. Pumped plug down to 4112' at 11:00 PM. Cement did not circulate. 4. Ran Temperature survey. T.O.C940'. 5. Ran 200' 1" pipe outside 8-5/8" casing. Cemented w/150 sks. reg. 6. W.O.C. 32 Hrs. Tested casing w/1000# for 30 minutes.	•
3. Pumped plug down to 4112' at 11:00 PM. Cement did not circulate. 4. Ran Temperature survey. T.O.C940'. 5. Ran 200' 1" pipe outside 8-5/8" casing. Cemented w/150 sks. reg. 6. W.O.C. 32 Hrs. Tested casing w/1000# for 30 minutes.	•
3. Pumped plug down to 4112' at 11:00 PM. Cement did not circulate. 4. Ran Temperature survey. T.O.C940'. 5. Ran 200' 1" pipe outside 8-5/8" casing. Cemented w/150 sks. reg. 6. W.O.C. 32 Hrs. Tested casing w/1000# for 30 minutes.	•
3. Pumped plug down to 4112' at 11:00 PM. Cement did not circulate. 4. Ran Temperature survey. T.O.C940'. 5. Ran 200' 1" pipe outside 8-5/8" casing. Cemented w/150 sks. reg. 6. W.O.C. 32 Hrs. Tested casing w/1000# for 30 minutes. 7. Drill out plugs at 4112' & 4165'.	•
3. Pumped plug down to 4112' at 11:00 PM. Cement did not circulate. 4. Ran Temperature survey. T.O.C940'. 5. Ran 200' 1" pipe outside 8-5/8" casing. Cemented w/150 sks. reg. 6. W.O.C. 32 Hrs. Tested casing w/1000# for 30 minutes.	•
3. Pumped plug down to 4112' at 11:00 PM. Cement did not circulate. 4. Ran Temperature survey. T.O.C940'. 5. Ran 200' 1" pipe outside 8-5/8" casing. Cemented w/150 sks. reg. 6. W.O.C. 32 Hrs. Tested casing w/1000# for 30 minutes. 7. Drill out plugs at 4112' & 4165'.	•
3. Pumped plug down to 4112° at 11:00 PM. Cement did not circulate. 4. Ran Temperature survey. T.O.C940°. 5. Ran 200° 1° pipe outside 8-5/8° casing. Cemented w/150 sks. reg. 6. W.O.C. 32 Hrs. Tested casing w/1000# for 30 minutes. 7. Drill out plugs at 4112° & 4165°.	•
3. Pumped plug down to 4112' at 11:00 PM. Cement did not circulate. 4. Ran Temperature survey. T.O.C940'. 5. Ran 200' 1" pipe outside 8-5/8" casing. Cemented w/150 sks. reg. 6. W.O.C. 32 Hrs. Tested casing w/1000# for 30 minutes. 7. Drill out plugs at 4112' & 4165'.	•
3. Pumped plug down to 4112' at 11:00 PM. Cement did not circulate. 4. Ran Temperature survey. T.O.C940'. 5. Ran 200' 1" pipe outside 8-5/8" casing. Cemented w/150 sks. reg. 6. W.O.C. 32 Hrs. Tested casing w/1000# for 30 minutes. 7. Drill out plugs at 4112' & 4165'.	•
3. Pumped plug down to 4112° at 11:00 PM. Cement did not circulate. 4. Ran Temperature survey. T.O.C940°. 5. Ran 200° 1° pipe outside 8-5/8° casing. Cemented w/150 sks. reg. 6. W.O.C. 32 Hrs. Tested casing w/1000# for 30 minutes. 7. Drill out plugs at 4112° & 4165°.	•