INCLINATION REPORT

ONE COPY OF BE FILED WITH EACH COMPLETIC REPORT

Field Name		County		RRC Dist. No.	···
Operator <u>Midwest Oi</u>	l Corporation	Address 1507 Walk	oo Building	City_Midland,	Texas
Lease Name & No. 4		Well No. 1		Survey	
		CORD OF INCLINATION		:1 o +	
Depth (feet) 9585 9090 9265 9405 9610 10070 10150 10500 10635 10700 10775 TD	Angle of Inclination (d) 1 1/2 2 1/1 2 3/1 2 1/2 2 1 1/2 2 1 1/1 1	egrees) Displaceme	98 15 83 10 15 05 79 63 36	Accumulative Displacement (f 111.16 130.61 139.19 145.59 152.71 161.79 167.58 175.21 177.57 178.71 180.02	
			tal Displacem		-
Was survey run in Tu Distance to nearest Distance to lease li Certification of per I hereby cert form, and that such	lease line nes as prescribed sonal knowledge In	feet by field rules	omplete.		, -
CACTUS DRILLING 3				MCT TATE ON	
		Compai	пу 		
Operator Affidavit: (Note: Party making affidav	vit must strike out inappli	cable phrases, and must file	explanatory stater	ment when applicable	.)
anarater of the well identifie	ed in this instrument (that), and that such well was	personally appeared <u>Car</u> ibed hereto, who, after being he is acting at the direction not intentionally deviated frothe attached statement).	and on behalf of t	ne operator of the we	11
		Signa	ture and Titl	le of Affiant	
Sworn and Subs	cribed to before m	e, this the 19 Notax	day of S	September Ait(cur and for Midland	,
RRC Use Only:					
Approved By:					

FORMATION AND INSTRUCTIONS AS . . STATEWIDE RULE 54

II. INCLINATION SURVEYS

A. Requirement of

- l. An inclination survey made by persons or concerns approved by the Commission shall be filed on a form prescribed by the Commission for each well drilled or deepened with rotary tools or when as a result of any operation the course of the well is changed.
- a. The first shot point of such inclination survey shall be made at a depth not greater than 500 feet below the surface of the ground and succeeding shot points shall be made either at 500 foot intervals or at the nearest drill bit change thereto; but not to exceed 1000 feet apart.
- 2. Inclination surveys conforming to these requirements may be made either during the normal course of drilling or after the well has reached total depth. Acceptable directional surveys may be filed in lieu of inclination surveys.
- 3. Copies of all directional or inclination surveys, regardless of the reason for which they are run, shall be filed as a part of or in addition to the inclination surveys otherwise required by this rule.

B. Reports

- l. The report form prescribed by the Commission shall require that it be signed and certified by a party having personal knowledge of the facts therein contained.
- a. The report shall include a tabulation of the maximum drifts which could occur between the surface and the first shot point and each two successive shot points, assuming that all of the unsurveyed hole between any two shot points has the same inclination as that measured at the lowest shot point, and the total possible accumulative drift, assuming that all measured angles of inclination are in the same direction.
- 2. In addition, the report shall be accompanied by a sworn statement of the operator, or of someone acting at his direction on his behalf either, (1) that the well was not intentionally deviated from vertical whatsoever or, (2) that the well was deviated at random, with an explanation of the circumstances.
- 3. The report shall be filed in the District Office of the Commission for the district in which the well is drilled, by attaching one copy to each appropriate completion form for the well.
- 4. The Commission may require the submittal of the original charts, graphs, or discs resulting from the surveys.