

COUNTY	LEA	FIELD	Wildcat	STATE	NM
OPR	DELAWARE APACHE CORPORATION				
	1	Superior-State		CO-ORD	
	Sec. 17, T-13-S, R-36-E			MN	21737
	1980' FNL, 660' FWL of Sec.				
	Spd 4-2-66		CLASS	EL	
	Cmp 5-18-66		FORMATION	DATUM	FORMATION
CSG & SX - TUBING					
11 3/4" 360' 375					
8 5/8" 4600' 400					
4 1/2" 10600' 400					
LOGS EL GR RA IND HC A					
			TD 10600'		
PLUGGED & ABANDONED					

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Marcum Drlg. Co. PROP DEPTH 10,700' TYPE
 DATE

F.R. 3-24-66
 PD 10,700' - Penn.
 Contr. - Marcum
 4-4-66 Drlg. 1800'.
 4-11-66 Drlg. 5070'.
 4-18-66 Drlg. 7400', tight.
 4-25-66 Drlg. 9441' lm & sh., tight.
 5-2-66 Drlg. 10385' lm., tight.
 DST #1 10340-363', pkr failed.
 DST 10320-363', open 1 hr,
 rec 80' mud + 20' O&GCM,
 45 min IS IP 1154#, FP 46-46#, 1 hr
 FSIP 694#; HP 4903-4814#.
 5-9-66 TD 10600', tight.

5-9-66 Continued
DST 10357-430', open 2½ hrs,
Rec 200' mud + 1144' sul wtr,
45 min ISIP 3760#, FP 138-625#,
2½ hr FSIP 3422#; HP 4859-4814#.
Drld to 10600'
5-16-66 TD 10600', tight.
5-23-66 TD 10600', PLUGGED & ABANDONED.
(Holding for additional information)
5-31-66 TD 10600', COMPLETION REPORTED.
Perf 10340-354' W/4 SPF
Ac (10340-354') 3000 gals.
Swbd 46 BAW + 42 BLO/12 hrs, w/sli
show gas
Swbd 26 BAW + 18 B Salt Wtr in 7 hrs.
Swbd dry, s/skim of oil & very sli show
gas.

Att. Ac. (10340-354') 5000 gals.
Tubing split
Ac (10340-354') 20,000 gals + 48 Bbls
Kerosene + 48 Bbls Brine Wtr
Swbd 216 B Salt Wtr in 11 hrs, NS.
Swbd 41 B Salt Wtr in 2 hrs, NS.
LOG TOPS: Abo 8050', Abo Red Shale
8139', Wolfcamp Shale 10067', C-1
10332', C-2 10380'.