

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

OFFICE OF THE O.C.C.

JUL 7 11 50 AM '69

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-7272
7. Unit Agreement Name
8. Farm or Lease Name Lea IV State
9. Well No. 1
10. Field and Pool, or Wildcat Lazy J Penn
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT..." (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Gulf Oil Corporation
3. Address of Operator Box 670, Hobbs, New Mexico 88240
4. Location of Well UNIT LETTER P 660 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 26 TOWNSHIP 13-N RANGE 33-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4204' GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

Plugged and Abandoned

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9917' TD.

Ran tubing to 9767'. Circulated hole with mud. Raised tubing to 9700' and spotted 25 sack cement plug No. 1 from 9700' to 9500'. Checked free point of 5-1/2" casing and shot casing at 4986'. Recovered casing. Ran tubing and spotted 30 sack cement plug No. 2 from 5036' to 4936' across 5-1/2" casing stub at 4986'. Raised tubing and spotted 40 sack cement plug No. 3 from 4250' to 4150' across 8-5/8" casing shoe at 4200'. Located free point of 8-5/8" casing and shot casing at 1089'. Recovered casing. Spotted 50 sack cement plug No. 4 from 1139' to 1039' across 8-5/8" casing stub at 1089'. Spotted 65 sack cement plug No. 5 from 425' to 325' across 13-3/8" shoe at 374'. Spotted 40 sack cement plug No. 6 from 50' to surface. Installed dry hole marker. Plugged and abandoned July 3, 1969. Will advise when location is ready for inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY
C. E. MACE

SIGNED _____

TITLE **Area Petroleum Engineer**

DATE **July 7, 1969**

APPROVED BY **John W. Runyan**

TITLE **Geologist**

DATE **AUG 12 1969**

CONDITIONS OF APPROVAL, IF ANY: