

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Getty Oil Company
3. ADDRESS OF OPERATOR
P. O. Drawer DD, Levelland, Texas 79336
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980' FNL & 660' FEL, Section 35-13S-33E
AT SURFACE: 4197' F.L.
AT TOP PROD. INTERVAL: 9690-9864'
AT TOTAL DEPTH: 9880'
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE

NM - 01124

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Willard Beaty

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Lazy "J" Penn

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 35-13S-33E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

4208' K.B.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The following procedure was verbally approved by Armando Lopez on 1-27-83. Notify J. Gramham. Pressure annulus to 800 psi (Make sure able to squeeze). RIH w/ work string & cement retainer. Set retainer at 2990'± in 8 5/8" casing. Squeeze 100 sks (class "C") below retainer. Pull out and leave 3-5 sks on top of retainer. Pull up hole two joints and reverse cement out. Circulate 9.5 lb. mud. POH. RIH w/ csg gun. Perforate 8 5/8" casing at 1750' with 4 shots. POH w/ gun. RIH w/ work string and cement retainer. Set retainer @ 1650'±. Squeeze (95 sks class "C" cement) w/ 64 sks outside, 26 sks below retainer. Pull out and leave 3-5 sks on top of retainer. Pull up hole 2 jts and reverse out cement. Circulate 9.5 lb mud to surface. Cut off casing 4' below surface and lay 20 sks of cement inside and on top of 8 5/8" casing. Back fill & clean-up location. Place dry hole marker.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Clark Richards

TITLE Operating Engineer

DATE

2-9-83

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

FEB 22 1983

FEB 24 1983

*See Instructions on Reverse Side

JAMES A. GILLHAM
DISTRICT SUPERVISOROIL & GAS
ENGINEER
FEB 17 1983

RECEIVED
FEB 25 1989
D.C.D.
HOBBS C-102