

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION  
APR 17 8 25 AM '67

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Wilbo "A"
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat
12. County Lea

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>
2. Name of Operator EASON OIL COMPANY
3. Address of Operator % CIMA CAPITAN, INC. Box 1343, Artesia, New Mexico, 88210
4. Location of Well UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 22 TOWNSHIP 13 S RANGE 33 E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4235 GR 4253 KB

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

In accordance with verbal approval by MR E.F. ENGBRECHT, this well was plugged and abandoned on March 22, 1967, as follows:

Pulled and recovered 3715' 4-1/2" casing and 1250' 9-5/8" casing. Cement plugs were spotted at following depths:

25-sack plug at 5050 (bottom of 4-1/2"); 25-sack plug at 3715' (Top 4-1/2" which is inside 9-5/8"); 25-sack plug at 1250' (top 9-5/8" casing); 25-sack plug at 350' (bottom 13-3/8" casing) and 10-sack plug at top 13-3/8" casing) Set regulation marker. Mud-laden fluid was placed between cement plugs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Agent DATE 14 Apr 67

APPROVED BY [Signature] TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: