NO. OF COPIES RECEIVED		_
DISTRIBUTION		_
SANTA FE		_
FILE		_
U.S.G.S.		
LAND OFFICE		-
OPERATOR		-

(DO NOT USE TH

<u>West</u>

NO

OIL X
WELL X

2. Name of Operator

3. Address of Operator

4. Location of Well

EMPORARILY ABANDON

Service of the servic	Form C-103
NEW MEXICO OIL HURBS OFFICE Q. C. C.	Supersedes Old C-102 and C-103
	Effective 1-1-65
Jan 13 11 20 AM '67	State Fee. 5. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS IS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
GAS WELL OTHER-	7. Unit Agreement Name
EASON OIL COMPANY	8. Farm or Lease Name
	Wilbo A 9. Well No.
Cima Capitan, Inc. Box 1343, Artesia, New Mexico	3. WALL NO. 1
C 660 FEET FROM THE NORTH LINE AND 1980 FEET FROM	10. Field and Pool, or Wildcat Wildcat
LINE, SECTION 22 TOWNSHIP 13S RANGE 33E NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	
4235 GR 4253 KB	12. County
Check Appropriate Box To Indicate Nature of Notice, Report or Other TICE OF INTENTION TO:	Lea Million Para Para Para Para Para Para Para Par
PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPNS. CHANGE PLANS CASING TEST AND CEMENT JQB X	ALTERING CASING PLUG AND ABANDONMENT
OTHER	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Drilled 8-3/4" hole to 13240" total depth on Jan. 3, 1967.

DST No. 1 5 Dec. 66: 10573"- 10615'. Rec. 60' SGCM. 60 min. ISIP 366. IFP 68.

FFP 66. 2 hr. FSIP 619. FHP 5079.

DST No. 2 31 Dec 66: 12958-12980'. Rec. 7420' salt water plus 3500' water blanket.

60 min. ISIP 4919. 2 hr. FSIP 4919. IFP 1868. FFP 4881. FHP 6260.

DST No. 3. 5 Jan 67. Straddle Test. 13118-13166'. Rec. 4100' water blanket plus 700' salt water. IHP 6347. 60 min. ISIP4934. IFP 1804. FFP 2092. 3hr. FSIP 4790.

FHP 6304 Rw .22 @ 44°. Chlorides 35000.

In accordance with verbal approval from Mr. E. F. Engbrecht, cement plugs were set as follows on 8 Jan 67 (25 sacks per plug): 13240, 12950, 9660, 9000, 7550, 6820, 5370. With verbal approval, casing was run and cemented as follows: 9 Jan 67 ran 154 joints - 5080.82' 4-1/2" 9.5# ST&C J-55 SmIs casing. Landed 18.00' below KB. Bottom Guide shoe at 5099.82'. Float at 5065.24'. (PBTD). Cemented with 350 sacks 50-50 Posmix w/2% gel & 7# salt/sack. Plug down 11:50 AM. Tested casing to 1500 psi. Held OK. Float held OK. WOC.

18. I hereby certify that the information a	above is true and complete to the best of my knowledge and belief.	
SIGNED ACTORIO	TITLE Agent	. DATE 11 Jan 67
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	ORIGINAL & THREE COPIES SIGNED, BY: ERIC F. ENGERECTS' ENGINEER DISTRECT No. 1	JAN 16 1967