

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-025-21923

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
VA-5

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER RE-ENTRY

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter F : 2080 Feet From The North Line and 1980 Feet From The West Line

Section 32 Township 13S Range 34E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4157.6' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ☐ ALTERING CASING ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐ CASING TEST AND CEMENT JOB ☐
OTHER: ☐ OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-20-90. Cleaned location. Dug out cellar. RU pulling unit.
3-24-90. Drilled cement to 500'. Tested to 500 psi, OK. Drilled retainer and cement to 2560'. Tested to 500 psi, OK.
3-25-90. Drilled retainer at 4214' and cement to 4360'. Tested to 500 psi, OK.
3-26-90. Drilled retainer and cement to 8000'. RIH to CIBP at 10376'. Drilled CIBP at 10200' and pushed to 10376'.
3-28-90. Drilled retainer at 10402' and cement to 10501'. Cleaned out to 10808'. Set cement retainer 10200'. Pressured annulus to 500 psi. Squeezed perms 10255-308' w/50 sx Class H w/.6% Halad-9 and 25 sx Class H Neat. Squeezed to 3700 psi with 30 sx in formation. Tag cement retainer at 10202'. Drilled cement retainer 4-1/2 hrs, 20' of cement in 2-1/2 hrs. Not making any hole. POH.
3-30-90. TIH and drilled cement to 10315'. Circulated clean and POH. TIH w/sand drill tool. Cut 3 holes at 10653'. Spot 500 gals 20% NEFE acid. Would not take acid. Re-spot 500 gals acid, pressure tbg to 500 psi, no bleed off.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 4-3-90

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE APR 5 1990

CONDITIONS OF APPROVAL, IF ANY: