

COUNTY	LEA	FIELD	Lazy J	STATE	NM
CORP	SKEFELT OIL COMPANY			MAP	
	4 Beaty, Willard				
	Sec. 35, T-13-S, R-33-E			CO-ORD	
	660' ESL, 660' FEL of Sec.			MN 21929	
	Spd 11-18-66			CLASS EL [REDACTED]	
	Cmp 1-5-67				
	FORMATION		DATUM	FORMATION DATUM	
CSG & SX - TUBING					
11 3/4"		370'	400		
8 5/8"		4200'	800		
5 1/2"		9960'	500		
LOGS EL GR RA IND HC A					
TD 9960', PED 9921'					
TP Pennsylvanian Perfs 9890-9910' Flwd 368 BOPD. Pot. Based on 24 hr test thru 30/64" chk., TP 250#.					

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT	PROP DEPTH 9900'	TYPE RT
DATE		

F.R. 11-25-66
PD 9900' - Penn.

11-28-66 TD 4200', pulling 8 5/8" casing.
8 5/8" casing parted.

12-3-66 TD 4200', CO @ 2573'

12-10-66 TD 4200', WOC.
Re-Set 8 5/8" casing @ 4200' W/800 sx.

12-17-66 Drlg. 6345' dolo.

1-3-67 TD 9960', running 5 1/2" casing.
DST 9699-9820', open 2 hrs 20 mins,
Rev out 3 BO&GCM + 105 Bbls Salt Wtr,
1 hr ISIP 3234#, FP 1046-2774#,
1 hr FSIP 3050#.
DST 9820-9960', open 3 hrs,
Unloaded 35 BO while taking ISIP,
CTS 5 mins, OTS 20 mins,
Flwd 46 BO 1st hr; Flwd 36 BO 2nd hr;
Flwd 26 BO last 30 mins, SFP 300#,
Rev out 35 BO,
1 hr ISIP 2744#, FP 1793-1929#,
1 hr FSIP 427#.

IEA Larry J NM Sec. 35-13S-33E
SKEELY OIL CO., #4 Beaty, Willard Page #2

██████████-67 TD 9960', WOC.
1-16-67 TD 9960', PBD 9921', COMPLETE
Perf 9890-9901', 9906-10' W/2 SPF
Acid (9890-9910') 500 gals.
LOG TOPS: Bough "A" 9708', Bough "B"
9769', Bough "C" 9835', Cisco 9924'.