Submit 3 Copies

State of New Mexico En , Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

to Appropriate District Office

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION P.O. Box 2088

WELL API NO. 30-025-22239

DISTRICT II Santa Fe, New Mexico 87504-208 P.O. Drawer DD, Artesia, NM 88210	5. Indicate Type of Lease STATE FEE [X]
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BAD DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)	CK TO A 7. Lease Name or Unit Agreement Name
1. Type of Well: OR. GAS WELL X WELL OTHER	Sanders AOU
2. Name of Operator YATES PETROLEUM CORPORATION	8. Well No.
3. Address of Operator	9. Pool name or Wildcat
105 South 4th St., Artesia, NM 88210	Saunders Permo Upper Penn
4. Well Location	
Unit Letter F : 1980 Feet From The North Line a	nd 1980 Feet From The West Line
Section 1 Township 14S Range 33	E NMPM Lea County GR, etc)
Check Appropriate Box to Indicate Nature of NOTICE OF INTENTION TO:	Notice, Report, or Other Data SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL	WORK ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS COMMENC	CE DRILLING OPNS. PLUG AND ABANDONMENT [_]
	EST AND CEMENT JOB
OTHER:	Production casing & cement X
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent work) SEE RULE 1103. TD 10101'. Reached TD at 3:00 AM 12-8-95. Ran 244 follows: 14 joints of 5-1/2" 20# L-80 sandblasted L-80 varnished (2164.38'); 118 joints of 5-1/2" 17# of 5-1/2" 17# L-80 varnished (2396') and 1 joint of (Total 10064.80') of casing set at 10101'. Float set at 10016'. DV tool set at 7392'. Short joint stages as follows: Stage 1: 575 sacks Super Prems 5/10% Halad 344 and 4/10% CFR3 (yield 1.67, weight not bump plug. Circulated 60 sacks. Circulated the 635 sacks Premium Halliburton Lite with 3#/sack sain with 100 sacks Premium Neat (yield 1.18, weight plug to 3400 psi for 1 minute, OK. WOC.	# joints of 5-1/2" 17# & 20# casing as (558.46'); 53 joints of 5-1/2" 20# # J-55 varnished (4904.99'); 58 joints # 5-1/2" 20# L-80 varnished (40.97') # shoe set at 10100'. Float collar # set at 9604'. Cemented in two # ium, 5#/sack gilsonite, 1# salt, # 13.0). PD 11:00 PM 12-8-95. Did # prough DV tool for 4 hours. Stage 2: # It (yield 2.04, weight 12.4). Tailed
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	10.11.05
ι ι	uction Clerk 12-14-95
TYPEOR PRINT NAME Rusty Klein	теј ерноне но. 505/748-1

471 2810.50 (This space for State Use) · 对条线等 · 2000 · 2008 OFC 18 1995

me -

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY -