

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0228436-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Amerada Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

E1/2NE1/4 Sec. 31

T. 14S, R. 35E, NMPM

12. COUNTY OR PARISH

Lea

13. STATE

New Mex.

1.

OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

Olen F. Featherstone

3. ADDRESS OF OPERATOR

239 Petroleum Building, Roswell, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1930' FNL, 660' FEL Section 31, T. 14S, R. 35E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4045 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Oct. 3, 1967 Well spudded.

Oct. 4, 1967 Set 370' (GR) 13-3/8 H-40 48# surface casing.
Cemented 310 sacks 4% gel, 50 sacks encore 2% CaCl₂.
Circulated out 25 sacks. WOC 14 hours and pressure tested
1000# for 30 minutes with no drop.

Oct. 3, 1967 TD 4500'. Ran 4500' 8-5/8" intermediate casing as follows:

1165' 32# J-55 Top

2463' 24# J-55 Middle

867' 32# J-55 Bottom

Cemented with 400 sacks cement 16% gel, followed by 100
sacks neat cement on bottom. WOC 18 hours and pressure
tested 1500# for 30 minutes with no pressure drop.

18. I hereby certify that the foregoing is true and correct

SIGNED Charles W. HicksTITLE General ManagerDATE Oct. 12, 1967

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

*See Instructions on Reverse Side

OCT 13 1967

J L GORDON
ACTING DISTRICT ENGINEER