

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator The Superior Oil Company		8. Farm or Lease Name Agnes Malone
3. Address of Operator P. O. Box 1900, Midland, Texas 79701		9. Well No. 1
4. Location of Well UNIT LETTER J 2310 FEET FROM THE South LINE AND 1650 FEET FROM THE East LINE, SECTION 11 TOWNSHIP 14-S RANGE 37-E NMPM.		10. Field and Pool, or Wildcat Wildcat - Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) Est. 3840 KB		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well spud date is midnight on 3/9/68. Drilled 17-1/2" hole to 325' and ran 13-3/8", 48.0#, H-40 casing to 325'. Cemented casing with 475 sacks regular cement with 2% CaCl. Cement job completed at 3:15 P.M. on 3/10/68 with good cement returns, FP = 1000 psi. Installed casinghead, nipped up BOP and tested to 1000 psi. Test held OK. WOC for 39 hours and drilled out with 12-1/4" bit at 7:00 A.M. on 3/12/68.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED L. D. Blay TITLE Petroleum Engineer DATE March 12, 1968

APPROVED BY [Signature] TITLE DATE 1968

CONDITIONS OF APPROVAL, IF ANY:

