

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION, C. C.

MAY 17 11 30 AM '68

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Delaware-Apache Corporation	8. Farm or Lease Name State - 30
3. Address of Operator 1720 Wilco Building, Midland, Texas	9. Well No. 1
4. Location of Well UNIT LETTER N , 660 FEET FROM THE east LINE AND 1900 FEET FROM THE north LINE, SECTION 30 TOWNSHIP 13E RANGE 33E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4275.3 GL	12. County Lee

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-10-68 - Verma Drilling Co. spudded 15" hole at 8:00 p.m. 5-8-68. Drld. 355'.
Ran 9 jts 11 3/4" casing set at 352'. Cemented with 175 sac w/4% gal
and 2% CaCl. 150 sac Mast w/2% CaCl. Plugged down at 10:30 a.m.
Tested 11 3/4" casing and BOPs w/600 psi for 30 minutes, held O.K.

5-16-68 - Ran 77 jts 320 and 61 jts 240 & 5/8" csg. 11" hole, set at 4096'.
Cemented w/250 sac Class C w/8% gal plus 2% NaCl plus 150 sac Incor
plus 2% CaCl. Plugged down at 7:30 a.m. W.O.C. 18 hrs., tested
8 5/8" csg. and BOPs 1600 psi for 30 minutes, held O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNED <u>L.B. Williams</u>	TITLE <u>Area Engineer</u>	DATE <u>May 16, 1968</u>
APPROVED BY <u>John W. Runyan</u>	TITLE <u>Geologist</u>	DATE <u></u>
CONDITIONS OF APPROVAL, IF ANY:		