

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No. E-8956	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER DRY ZONE		7. Unit Agreement Name
2. Name of Operator Amoco Production Company		8. Farm or Lease Name STATE "A2"
3. Address of Operator BOX 68, HOBBS, N. M. 88240		9. Well No. 4
4. Location of Well UNIT LETTER A 990 FEET FROM THE NORTH LINE AND 990 FEET FROM THE EAST LINE, SECTION 34 TOWNSHIP 12-S RANGE 34-E NMPM. RANGER LAKE - BOUGH		10. Field and Pool, or Vicinity
15. Elevation (Show whether DF, RT, GR, etc.) 4169' R.D.B.		12. County LEA

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER ☐	PLUG AND ABANDON ☒ CHANGE PLANS ☐ OTHER ☐
REMEDIAL WORK ☐ COMMENCE DRILLING OPNS. ☐ CASING TEST AND CEMENT JOBS ☐ OTHER ☐	
ALTERING CASING ☐ PLUG AND ABANDONMENT ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) (SEE RULE 1103.)

Propose to plug and abandon well as follows:
 Spot 50 54 cement plug across perfs (9923-10,115). TCMT Est back to 9700.
 Shoot and pull 5 1/2" casing from free point. (Est 7000 - 6500')
 Spot 35 54 cement plug @ 15700'.
 in & out of 8 5/8" CSA 4196.
 Shoot and pull 8 5/8" casing @ free point. (Est 1500 - 1800')
 Spot 50 54 cement plug in & out of 8 5/8" stub.
 " 10 " " " @ surface and erect P&A marker.
 All intervals to be filled w/ heavy mud laden fluid.
 Final cleanup shall be made and ground restored to contour.
 100' Plug in & out stub 5 1/2" All Plugs must be
 PBD-12660 (CIBPC @ 12700' 440' cement Cap) 100' - Except surface
 of 105Ks JAR

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED _____ TITLE **AREA SUPERINTENDENT** DATE **MAR 16 1972**

0+2 NMOC-H
 APPROVED BY
 1- DTU
 CONDITIONS OF APPROVAL, IF ANY:
 1- SUSP
 1- RRV

Orig. Signed by
 John Ryan
 Geologist

TITLE _____ DATE **MAR 20 1972**

RECEIVED

MAR 17 1970

OIL CONSERVATION COMM.
ROBES. N. M.