

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. NM2842-A
2. NAME OF OPERATOR Coastal States Gas Producing Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 235, Midland, Texas 79701		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface		8. FARM OR LEASE NAME Federal #10
14. PERMIT NO. 660' FSL & 1980' FWL, Sec 20, T-13-S, R-33-E, Lea Co., NM		9. WELL NO. 2
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4256' GR		10. FIELD AND POOL, OR WILDCAT North Loma (Upper Penn)
		11. SEC., T., R. M., OR S. K. AND SURVEY OF AREA Sec 20, T-13-S, R-33-E
		12. COUNTY OR PARISH Lea
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT	
TEST WATER SHUT-OFF	☐	WATER SHUT-OFF	☐
FRACTURE TREAT	☐	FRACTURE TREATMENT	☐
SHOOT OR ACIDIZE	☐	SHOOTING OR ACIDIZING	☐
REPAIR WELL	☐	(Other)	☐
PULL OR ALTER CASING	☐	REPAIRING WELL	☐
MULTIPLE COMPLETE	☐	ALTERING CASING	☐
ABANDON*	☒	ABANDONMENT*	☐
CHANGE PLANS	☐		

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and open-pertinent to this work.)*

Well No. 2 is no longer economical to produce and is to be plugged and abandoned as follows:

1. Place 10' cmt on top of Otis PL Pkr set @ 9585'. Pkr is equipped with type N plug.
2. 25 sxs @ 5-1/2" stub.
3. 35 sxs @ top of Glorieta (4790') if exposed.
4. 50 sxs in and out of 8-5/8". Shoe @ 4080'.
5. 25 sxs @ 8-5/8" stub.
6. 25 sxs @ top of salt (1660') if exposed.
7. 35 sxs in and out of 13-3/8". shoe @ 362'.
8. 10 sxs in top.
9. Install DHM.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE **Division Production Manager**

DATE **3-9-71**

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

MAR 10 1971

R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse

General: This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local, area, and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions. Consult local

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents; not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1961-O-685229

APPROVED

ARTHUR R. BROWN
DISTRICT ENGINEER

10 MAR 1 0 1971

IS-6000 - NO. 1000 - **RECEIVED**

100-443886-100

BY _____

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SPRING NOTICES AND REPORTS ON WELLS

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

162-2, 11-13-14
157-1, 11-13-14