

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K 4421	

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- <u>Dry</u>		7. Unit Agreement Name
2. Name of Operator Cayman Corporation		8. Farm or Lease Name Humble State
3. Address of Operator 1123 Wilco Bldg., Midland, Texas 79701		9. Well No. 2
4. Location of Well UNIT LETTER <u>E</u> , <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>32</u> TOWNSHIP <u>13S</u> RANGE <u>37E</u> NMPM.		10. Field and Pool, or Wildcat <u>Wildcat</u>
15. Elevation (Show whether DF, RT, GR, etc.) <u>3888.8 GR</u>		12. County <u>Lea</u>

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-18-68 Placed 25 sack cement plugs at:  
11,183 - 11,283 8,253 - 8,353  
10,567 - 10,667 5,785 - 5,885  
9,775 - 9-875 4,620 - 4,720

1- 8-69 Shot into and recovered 1507' of 8 5/8", 24# casing.  
Placed cement plugs at:  
1475 - 1525 25 sx  
370 - 410 25 sx  
surface 10 sx  
Installed marker  
9.0 lb per gal mud between all cement plugs

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. Woodrich TITLE Engineer DATE 1-17-69  
APPROVED BY John W. Runyan TITLE Commissioner DATE 1-17-69  
CONDITIONS OF APPROVAL, IF ANY: