NO. OF COPIES P	PECEIVED					Form C-103				
DISTRIBU	TION		v			Supersedes Ol C-102 and C-1				
SANTA FE	A FE NEW MEXICO OIL CONSERVATION COMMISSION				Effective 1-1-6					
FILE						1				
U.S.G.S.						5a, Indicate Type	of Lease			
LAND OFFICE	<u>-</u>					State	Fee X			
OPERATOR						5. State Oil & Gas	3 Lease No.			
(DO NOT	USE THIS FORM F	UNDRY NOTICES A	ND REPORTS ON OR TO DEEPEN OR PLUG (FORM C-101) FOR SL	NWELLS	ERENT RESERVOIR.					
1. OIL WELL	GAS WELL	OTHER-				7. Unit Agreement	Name			
2. Name of Opera			• • • • • • • • • • • • • • • • • • •			8. Farm or Lease	Name			
OL	EN F. FE	ATHERSTONE				ELKAN				
3. Address of Ope	erator	· · · · ·				9. Well No.				
2 3	9 Petrol	eum Building	g, Roswell,	New Mex	ico 88201	1				
4. Location of We	11					10. Field and Poo	l, or Wildcat			
UNIT LETTER	G	1980 FEET	North	1 140 440	1980	WILDCA	T			
UNIT CETTER										
E.	ast	11 SECTION	14	S.	34 E.	(()))))))))))))))))))))))))))))))))				
	CINE,	SEC (104	I OWNSHIP	RANGE	N.N.	ו••• (())))))))				
			levation (Show whethe ,101' GR.	r DF, RT, GR,	etc.)	12. County LEA				
16.	Ch	eck Appropriate I	Box To Indicate	Natura of N	ation Papart or	Other Date				
		OF INTENTION TO				INT REPORT OF:				
PERFORM REMEDIA	AL WORK		PLUG AND ABANDON	REMEDIAL W		ALTERI	NG CASING			
TEMPORARILY ABA	NDON			COMMENCE D	RILLING OPNS.	PLUG A	ND ABANDONMENT			
PULL OR ALTER CA			CHANGE PLANS	CASING TEST	AND CEMENT JOB					
				OTHER						
OTHER										
		(0)		1,,	·····		<u> </u>			
17. Describe Prop work) SEE RI		ted Operations (Clearly	⁷ state all pertinent de	tails, and give	pertinent dates, includ	ling estimated date of s	tarting any proposed			
,		SI	URFACE	,						
12-26-68										
12-27-68	Total D	epth - 410',	. Ran 12 ja	oints (4	10') new 12	-3/4" 28 # s	urface			
		pipe and cemented with 400 sacks Incor with 2% $CaCl_2$. Cement cir-								
		. Plug down								
12-28-68	10:30 A	.M. pressure	e tested 10(00# for	30 minutes	with no prea	ssure loss.			
	Began d	rilling.								
			NTERMEDIATE							
1-6-69		Total Depth - 4,500'. Ran 4,500' new 8-5/8" 24# and 32# K55 and $28\#$								
							pozmix follov			
	ed by 2	00 sacks Cla	ass C with 2	2% CaCl,	. Plug dow	n 8:20 P.M.	Calculated			
	top of	cement - 235	50' from su	rface, ²						
1-7-69	woc.									
1-8-69		e tested 150 M.)0∦ for 30 m	ninutes	with no los	s. Began d	rilling			
	•									

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Change SU Hickor	TITLE	General Manager	DATE	1-9-69
APPROVED BY	TITLE		DATE	