NO. OF COPIES RECEIVED DISTRIBUTION SANTA FE FILE	NEW MEXICO OIL CONSERVATION COMMISSION		Form C-103 Supersedes Old C-102 and C-103 Effective 1-1-55
FILE U.S.G.S.			5a. Indicate Type of Lease
LAND OFFICE		,	State X Fee
OPERATOR	- -		5. State Oil & Gas Lease No.
			K-3 643
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT " (FORM C-101) FOR SUCH PROPOSALS.)			
			7. Unit Agreement Name
WELL WELL OTHER. Dry Hole			
2. Name of Operator			8. Farm or Lease Name
Union Texas Petroleum Corporation			State "1"
3. Address of Cperator			9. Well No.
1300 Wilco Building, Midland, Texas			1
4. Location of Well			10. Field and Pool, or Wildcat
UNIT LETTER K	1980 FEET FROM THE South	LINE AND 1980 FEET FROM	Undesignated
	10N 1 TOWNSHIP 14-S		
15. Elevation (Show whether DF, RT, GR, etc.)			12. County
	4301 DF		Lea
16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
		000000000000000000000000000000000000000	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	EMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	cc	OMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT X
PULL OR ALTER CASING	CHANGE PLANS	SING TEST AND CEMENT JOB	
		OTHER	
OTHER			

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7-7/8" hole to total depth of 10,000'. Logged and ran DST's 9810'-72' 9886'-9920' and 9925'-10,000'. Spotted 163 sx cement plug from 10,000' to 9700'-covered "Bough" formation. Spot 25 sx plug at 9290' Wolfcamp. Spot 25 sx plug at 7540' ABO. Spot 25 sx plug at 4900' Glorietta. Spot 25 sx plug in bottom of 8-5/8" casing at 3994'. Cut 8-5/8" casing at 2600' and recovered 84 joints. Spot 50 sx cement plug at 2650' to 2550'. Spot 55 sx plug from 437' to 337' - 50' in and out of 11-3/4" surface casing at 387'. Spot 10 sx plug at surface. Installed dry hole marker. Hole filled with heavy mud between cement plugs.

Verbal permission to P & A received from L. A. Clements 1-20-69.