

COPIES RECEIVED	
DISTRIBUTION	
PANDA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	OG-5798

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input type="checkbox"/> OTHER- <b>Dry Hole</b>	7. Unit Agreement Name
2. Name of Operator <b>Hondo Oil &amp; Gas Company</b>	8. Farm or Lease Name <b>State "BK"</b>
3. Address of Operator <b>P. O. Box 1978, Roswell, New Mexico 88201</b>	9. Well No. <b>1</b>
4. Location of Well <b>L 1980 South 660</b> UNIT LETTER <b>L</b> FEET FROM THE <b>1980</b> LINE AND <b>660</b> FEET FROM <b>West</b> LINE, SECTION <b>3</b> TOWNSHIP <b>14-S</b> RANGE <b>34-E</b> N.M.P.M.	10. Field and Pool, or Wildcat <b>Undesig. Wfc/U. Penn.</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>4140' DF</b>	12. County <b>Lea</b>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

**This well has been plugged and abandoned by setting the following neat Incon cement plugs:**

40 sx 10380-10280 (Top of Penn)	40 sx 2928-2858 (9-5/8" csg stub)
40 sx 9735- 9635 (Top of Wfc)	25 sx 1885-1910 (Top of salt)
40 sx 7980- 7880 (Top of Abo)	35 sx 380- 430 (13-3/8" csg shoe)
40 sx 5790- 5690 (Top of Glorieta)	10 sx 15- 30
40 sx 4542- 4442 (9-5/8" csg shoe)	

9.8#/gal gel mud was used to spot all plugs. Cut & recovered 88 jts of 9-5/8" casing. 13-3/8" casing remains intact. Installed dry hole marker. Well P & A 2/9/69.

We will notify your office by letter when location is ready for inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original Signed SIGNED <b>O. D. Bratch</b>	TITLE <b>Dist. Drlg. Supervisor</b>	DATE <b>2-19-69</b>
APPROVED BY <b>John W. Runyan</b>	TITLE <b>Asst. Dir.</b>	DATE <b>2-22-69</b>
CONDITION OF APPROVAL, IF ANY:		