

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

3 - NMCC
1 - File

OFFICE OF THE O. C. C.

JUN 10 3 52 PM '69

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.		

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Getty Oil Company	8. Farm or Lease Name State BK Com.
3. Address of Operator Box 249, Hobbs, N. Mex.	9. Well No. 1
4. Location of Well UNIT LETTER B 660 FEET FROM THE north LINE AND 1980 FEET FROM THE east LINE, SECTION 12 TOWNSHIP 14S RANGE 32E NMPM.	10. UNDESIGNATED Basin Upper Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4277.4 GL	12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Drilled 7 7/8" hole to 10,605'. Set 5 1/2" 17 #J-55 and N-80 casing at 10,064'. Cemented w/200 sacks 50-50 Pennix Class H Cement, and 200 sacks Class H with .3 of 1% retarder. Temperature survey indicated top of cement behind 5 1/2" at 8700'. Released rig 9PM 5-16-69. On 5-23-69 ran Welox bond log and showed good cement below 8766'. Tagged bottom w/4-3/4" bit at 9994'. Tested 5 1/2" casing with 2000" for 30 minutes, no drop in pressure.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY:

C. L. Wade

SIGNED _____ TITLE **Area Supt.** DATE **6-9-69**

APPROVED BY _____ TITLE _____ DATE **1969**

CONDITIONS OF APPROVAL, IF ANY: