

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION C. C.
 6 - ~~RMOC~~
 1 - Mr. G. E. Truran - ~~Houston~~ ³ AM '69
 1 - Mr. J. E. Pierce - Midland
 1 - File

Form C-101
 Revised 1-1-65

5A. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name State NH Com.
9. Well No.
10. Field and Pool, or Wildcat UNDESIGNATED
12. County Lee
19. Proposed Depth 10,000
19A. Formation Upper Penn
20. Rotary or C.T. Rotary
21. Elevations (Show whether DF, RT, etc.) 4280.4
21A. Kind & Status Plug. Bond Blanket Bond
21B. Drilling Contractor Pending
22. Approx. Date Work will start July 20, 1969

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK					
1a. Type of Work b. Type of Well OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> SINGLE ZONE <input checked="" type="checkbox"/> MULTIPLE ZONE <input type="checkbox"/>					
2. Name of Operator Getty Oil Company					
3. Address of Operator P. O. Box 249, Hobbs, New Mexico 88240					
4. Location of Well UNIT LETTER F LOCATED 1980 FEET FROM THE North LINE AND 1080 FEET FROM THE West LINE OF SEC. 12 TWP. 14S RGE. 32E NMPM					
23. PROPOSED CASING AND CEMENT PROGRAM					

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
17 1/4"	13-3/8"	48	400	400	Surface
11"	8-5/8"	24 & 32	4100	765	Surface
7-7/8"	5-1/2"	17	10,000	300	9200' or 600' Above Bough C

It is proposed to drill a 17-1/4" hole using spud mud to 400', set 13-3/8" casing and circulate cement to surface. A 11" hole using brine will be drilled to 4100', where 8-5/8" casing will be set and cement circulated to surface. A 7-7/8" hole, using fresh water and mud to be drilled to 10,000'. Open hole logs to be run are Bone hole compensated Sonic-Gamma Ray from surface to TD, a dual induction Laterolog from 4100' to TD and a Microlog over prospective zones. The 5-1/2" casing to be set at 10,000 and cemented with 300 sacks cement. (Top of cement to be 600' above Bough "C".) A Gamma Ray-Neutron completion log will be run. Perforations in the Pennsylvanian to be picked after evaluation of logs is completed. Perforations to be treated with a cleanup acid stimulation.


THE COMMISSION MAY BE REQUESTED:

13 3/8
 TACKLING

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY: **C. L. Wade** Title **Area Supt.** Date **6-8-69**

(This space for State Use)
 APPROVED BY  TITLE **Joe Stanley** DATE **6-10-69**
 CONDITIONS OF APPROVAL, IF ANY: