STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

MOITUBIRTEID		
SANTA FE		
FILE		
V.S.O.S.		
LAND OFFICE		
00700700	7	

OIL CONSERVATION DIVISION P. O. BOX 2088 SANTA FE, NEW MEXICO 87501

Form C-103 Revised 10-1-78

Sa. Indicate Type of Lease State X Fee __ 5. State Oll & Gas Lease No. LG 3716 SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FIRM FOR PROPOSALS TO BRILL OR TO DEEPEN OR PLUG BACK TO A C
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSA 7. Unit Agreement Name WELL X Re-Entry OTHER. 8. Form or Lease Name 2. Name of Operator Midwest Hightower ADS St Yates Petroleum Corporation 9. Well No. 3. Address of Operator 207 South 4th St., Artesia, NM 88210 1 10. Field and Pool, or Wildcat 4. Location of Well Wildcat 660 South UNIT LETTER . 33E West 15. Elevation (Show whether DF, RT, GR, etc.) 12. County 4305.4' GR Lea Check Appropriate Box To Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: PLUS AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPNS. CASING TEST AND CEMENT JOB CHANGE PLANS OTHER Correction on 5-1/2" 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SER RULE 1103. CORRECTION ON 5-1/2" CASING. Ran 260 joints 5-1/2" casing as follows: 5-1/2" float shoe at 10489', 1 jt 20# P-110. Float collar at 10447'. Ran 19 jts 20# P-110; 1 jt 20# N-80 marker jt; 72 jts 20# P-110; 95 jts 17# J-55; 70 jts 17# N-80; and 2 jts 20# P-110. Cemented w/450 sx Class "H" + .7% CF-14 + .4% TR-4. Compressive strength of cement - 1750 psi in 12 hrs. PD 5:15 PM 2-3-86. WOC 18hrs. 18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Production Supervisor

ORIGINAL SIGNED BY JERRY SEXTON DISTRICT | SUPERVISOR

CONDITIONS OF APPROVAL, IF ANY:

Met 19 1986