

COUNTY	IEA	FIELD	Undesignated	STATE	NM	30-025-23640
OPR	BTA OIL PRODUCERS			MAP		
1 Wade 700-A						
Sec 35, T-12-S, R-37-E						
1830' FSL, 1980' FEL of Sec						
Spd 11-13-70						
Cmp 7-6-71						
				CLASS		
				EL 38862		
CSG & SX - TUBING				FORMATION	DATUM	FORMATION
2 3/4" at 430' w/400 SX						
8 5/8" at 4500' w/300 SX						
5 1/2" at 12,218' w/700 SX						
LOGS EL GR RA IND HC A						
				TD 12,279'; PBD 12,218'		
TEMPORARILY ABANDONED						

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Seating Service, Inc.

CONT. Hondo	PROP DEPTH	12,300'	TYPE	RT
DATE				

F.R. 11-24-70; Opr's Elev. 3876' JL
 PD 12,300' RT (Devonian)
 Contractor - Hondo

11-23-70 Drlg. 6065'
 12-1-70 Drlg. 8968'
 12-7-70 Drlg. 10,167'
 DST 9745-88', Pkrs Failed
 DST 9735-88', open 1 hr 10 mins, rec 150' sli
 O&GCM, 1 hr ISIP failed, FP 150-171#, 2 hr
 FSIP 1933#

12-14-70 Drlg. 11,090'
 12-21-70 Drlg. 11,910'
 1-5-71 TD 12,279'; WOO
 DST (Devonian) 12,218-275', Pkrs failed

1-5-71 Continued
DST (Devonian) 12,218-275', open 1 hr 10 mins,
rec 518' DM + 8902' salty sul wtr, 1 hr ISIP
2711#, FP 3138-3763#, 2 hr FSIP 4163#

1-12-71 TD 12,279'; SI
1-19-71 TD 12,279'; SI
2-22-71 TD 12,279'; SI
3-22-71 TD 12,279'; SI
3-29-71 TD 12,279'; PBD 12,218'; Prep Swab
Perf 11,490-498' w/2 SPF
4-5-71 TD 12,279'; PBD 12,218'; Prep Perf
Acid (11,490-498') 3500 gals
Swbd Dry (11,490-498')
4-13-71 TD 12,279'; PBD 12,218'; Swbg load

4-13-71 Continued
Perf 11,546-568' w/4 SPF
Acid (11,546-568') 1000 gals

4-20-71 TD 12,279'; PBD 12,218'; Tstg
Flwd 23 EF (92% salt wtr) in 7 hrs (11,490-498')

5-3-71 TD 12,279'; PBD 12,218'; SI
6-28-71 TD 12,279'; PBD 12,218'; SI
7-6-71 TD 12,279'; PBD 12,218'; TEMPORARILY ABANDONED
(May convert to WDW at later date.)
7-8-71 COMPLETION REPORTED