

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-4671
7. Unit Agreement Name
8. Farm or Lease Name State 1-21
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Meadco Properties, Ltd.
3. Address of Operator 407 West Wall St., Midland, Texas 79701
4. Location of Well UNIT LETTER M 660 FEET FROM THE South LINE AND 660 FEET FROM West THE LINE, SECTION 21 TOWNSHIP 14S RANGE 32E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4330.5' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/> CHANGE PLANS <input type="checkbox"/> OTHER <input type="checkbox"/>
REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input type="checkbox"/> OTHER <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/> OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plan to cut 4-1/2" casing at approximately 7300' and 8-5/8" casing at approximately 1500'.

Plugs will be spotted as follows:

- 25 sx on bottom
- 25 sx in and out of 4-1/2" casing stub
- 25 sx at top of Glorieta (approx. 5715')
- 25 sx at shoe of 8-5/8" casing
- 25 sx in and out of 8-5/8" casing stub
- 10 sx at surface.

Permanent marker will be installed.

25 sxs in front of 13 3/4 shoe

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNED <u>[Signature]</u>	TITLE <u>Petroleum Engineer</u>	DATE <u>12/8/71</u>
APPROVED BY <u>[Signature]</u>	TITLE <u>[Signature]</u>	DATE <u>DEC 10 1971</u>
CONDITIONS OF APPROVAL, IF ANY:		