

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
T. Anhy	1660	T. Canyon	9206	T. Ojo Alamo		T. Penn. "B"	
T. Salt	1750	T. Strawn		T. Kirtland-Fruitland		T. Penn. "C"	
B. Salt	2360	T. Atoka		T. Pictured Cliffs		T. Penn. "D"	
T. Yates	2468	T. Miss		T. Cliff House		T. Leadville	
T. 7 Rivers		T. Devonian		T. Menefee		T. Madison	
T. Queen	3170	T. Silurian		T. Point Lookout		T. Elbert	
T. Grayburg		T. Montoya		T. Moncos		T. McCracken	
T. San Andres	3753	T. Simpson		T. Gallup		T. Ignacio Qtzte	
T. Glorieta	5140	T. McKee		Base Greenhorn		T. Granite	
T. Paddock		T. Ellenburger		T. Dakota		T.	
T. Ilinebry		T. Gr. Wash		T. Morrison		T.	
T. Tubb	6530	T. Granite		T. Todilto		T.	
T. Drinkard		T. Delaware Sand		T. Entrada		T.	
T. Abo	7306	T. Bone Springs		T. Wingate		T.	
T. Wolfcamp	8408	T.		T. Chinle		T.	
T. Penn.	8756	T.		T. Permian		T.	
T. Cisco (Bough C)	8878	T.		T. Penn. "A"		T.	

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1660	1660	Red sand and shale				
1660	1750	90	Anhydrite				
1750	2360	610	Salt				
2360	2468	108	Dolomite-Anhydrite				
2468	2592	124	Sand				
2592	3170	578	Dolomite and anhydrite				
3170	3753	583	Sand and dolomite				
3753	5140	1387	Dolomite				
5140	6530	1390	Dolomite and sand				
6530	6660	130	Sand				
6660	7306	646	Dolomite and shale				
7306	8408	1102	Dolomite-shale and lime				
8408	8756	348	Dolomite and shale				
8756	9206	450	Lime and shale				
9206	9845	639	Lime and shale				
9845	10050	TD205	Lime				

RECEIVED

SEP - 11 1971

**OIL CONSERVATION COMM.
HOBBS, N. M.**