

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
 Supersedes Old
 C-102 and C-103
 Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee
5. State Oil & Gas Lease No.	
K-6271	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Western States Producing Company	8. Farm or Lease Name Midwest State Com
3. Address of Operator 900 Building of the Southwest, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER P 660 FEET FROM THE South LINE AND 660 FEET FROM THE East LINE, SECTION 35 TOWNSHIP 13S RANGE 32E NMPM.	10. Field and Pool, or Well Name Baum Upper Permian
15. Elevation (Show whether DF, RT, GR, etc.) 4309 KB	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPER. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1109.

- Picked up 8-5/8" casing. Shot casing at 1600', 1250', and 1017'.
- Recovered 1017' of 8-5/8" casing, left 3027' in well.
- Conditioned hole with 10.0#/gal. salt Gel mud and spotted 25-sack cement plug at 1020', 25-sack plug at 462' to 362' in 13-3/8-inch casing, and 10-sack plug from 40' to surface.
- Cut off well head, welded on plate and installed dry-hole marker. Complete 2-11-72.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Don C. Bennett</u>	TITLE <u>Vice President</u>	DATE <u>September</u>
APPROVED BY <u>Nathan E. Vegg</u>	TITLE <u>OIL & GAS INSPECTOR</u>	DATE <u>MARCH 6 1972</u>
CONDITIONS OF APPROVAL, IF ANY:		