

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State ☐	Fee ☒
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL ON TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
(USE APPLICATION FOR PERMIT - 17 (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. Unit Agreement Name
2. Name of Operator		McDonald Unit
3. Address of Operator		8. Farm or Lease Name
P. O. Box 1933, Roswell, New Mexico 88201		3
4. Location of Well		9. Well No.
UNIT LETTER <u>M</u> 890 FEET FROM THE <u>South</u> LINE AND 467 FEET FROM		Wildcat
THE <u>West</u> LINE, SECTION <u>34</u> TOWNSHIP <u>13S</u> RANGE <u>36E</u> NMPM.		10. Field and Pool, or Wildcat
15. Elevation (Show whether DF, RT, GR, etc.)		Lea
3948		12. County
		Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	
		OTHER <u>Re-entry & Plug</u> ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1109.

1/29/83 Cut off 12 3/4" csg. Welded on 13-3/8 X 12" 3000 csg head.
2/01/83 NU Stripper rubber & power swivel. Strt drly cmt plug.
2/04/83 TIH to 985'. Drld & rotated to top of 8 5/8" csg stub @ 1072'.
2/06/83 RIHw/skirted mill. Hit bridge @ 910'. Mill sticking & DC's plugging pulled mill off bottom.
2/07/83 Continued drilling to 1045'. Last 10' drilled was solid Red-Bed.
2/08/83 Worked string up & down without touching 8 5/8" csg.
2/09/83 Mixed & spotted 65 sx class "C" cmt plug from 1040' to 940' (100') and a 65 sx Class "C" plug from 448' - 348', (100') and a 10 sx class "C" cmt plug @ surface all plugs spotted w/45 viscosity and 10.8 ppg mud. A steel plate will be welded accross 12 3/4" csg & a DH marker 4" OD extending 4' above GL.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ray T. [Signature] TITLE Reservoir Engineer DATE 2/18/83

APPROVED BY [Signature] TITLE OIL & GAS INSPECTOR DATE APR 7 1988