

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
J.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name <b>McClish</b>	
9. Well No. <b>1</b>	
10. Field and Pool, or Wildcat <b>Wildcat</b>	
15. Elevation (Show whether DF, RT, GR, etc.) <b>3948' G.L.</b>	
12. County <b>Lea</b>	

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator  
**Samedan Oil Corporation**

Address of Operator  
**2207 Wilco Building, Midland, TX 79701**

Location of Well  
UNIT LETTER **M**, **890** FEET FROM THE **South** LINE AND **467** FEET FROM  
THE **West** LINE, SECTION **34** TOWNSHIP **13-S** RANGE **36-E** NMPM.

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Hondo Drilling Company rigged up and spudded at 12:30 p.m. September 20, 1972. Drilled 17 1/2" hole to 396'. Ran 12 3/4" 34# J-55 casing, set at 396'. HOWCO cemented with 425 sacks Class "C" cement with 2% Ca Cl. Cement circulated. Plug down at 11:00 p.m. September 20, 1972. W.O.C. 18 hrs. and pressure tested casing for 30 min. with 1000#, no pressure loss. Drilling ahead.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

**William S. McCuen**  
SIGNED William S. McCuen TITLE **Production Superintendent** DATE **9-22-72**

APPROVED BY Joe D. Ramey DATE **SEP 25 1972**  
CONDITIONS OF APPROVAL, IF ANY: **Dist. I, Supv.**

RECEIVED

SEP 25 1972

OIL CONSERVATION COMM.  
HOUSTON, TEX.