

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		5. State Oil & Gas Lease No.
2. Name of Operator J. Lee Youngblood		7. Unit Agreement Name
3. Address of Operator 1965 First National Bank Bldg. - Dallas, Texas 75202		8. Farm or Lease Name Lowe
4. Location of Well UNIT LETTER H 1986 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 3 TOWNSHIP 13S RANGE 37E NMPM.		9. Well No. 1
15. Elevation (Show whether DF, RT, GR, etc.) 3890.3 GR		10. Field and Pool, or Wildcat WILDCAT
12. County Lea		

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-20-72 - Well spudded at 8:00 am. Drill 420' of 15" hole. Set 420' of 11 3/4", 42#, H40 new casing w/350 sxs and float valve. Good returns of cement at surface, estimated 15 sxs pumped to pit. Rule 107, Option 2: (1) 420 cf of Southwestern Portland, Class H with 2% CC, (2) 60° (3) 65°, (4) 1350# PSI, (5) 8 hrs. Pressured to 600# for 30" - no loss. Drilled out 2:30 am 9-21-72.

9-25-72 - Reached depth of 4530', 11" hole, in lime. Set 930' of K55-32# new, 1075' of H40-32# new and 2531' of K55-24# new casing - 8 5/8" (4536') at 4530' with 400 sxs cement with float valve. Option 2: (1) 480 cf of Southwestern Portland, Class H with 2% CC, (2) 55°, (3) 106°, (4) 2600# PSI, (5) 8 hrs. Pressured to 1,000# - no loss. Drilled out at 9:00 pm. All cement services performed by Halliburton Services.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Production Supt. DATE 10-04-72

APPROVED BY Joe D. Ramey TITLE Dist. I, Supv. DATE OCT 10 1972

CONDITIONS OF APPROVAL, IF ANY: