

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-2865

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Bell Petroleum Company	8. Farm or Lease Name Midwest State
3. Address of Operator P.O. Box 1538 Midland, Texas 79791	9. Well No. 1
4. Location of Well UNIT LETTER "B" , 660' FEET FROM THE North LINE AND 1980' FEET FROM THE East LINE, SECTION 19 TOWNSHIP 14S RANGE 33E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4249.8 GL, DF 4262'	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER Set 8 5/8" Csg. <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 134 jts. 8 5/8" csg. 4161'  
(70 jts. 8 5/8" csg. 32# @ 2197')  
(64 jts. 8 5/8" csg. 24# @ 1964')  
Set @ 4155' with Halliburton Guide shoe, Insert Float, 3 Centralizers & Fillup attachment with float.  
Cem. with 300 sax Class H Cement, 2 % Cal. Chloride.  
Plug down 11:15 AM 11-30-72  
WOC 18 hrs.  
Pressured up & Nippled up to 1000# for 30 min. Held OK

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Joan Fleming TITLE Production Supervisor DATE December 1, 1972

APPROVED BY Joe D. Ramey TITLE Dist. I, Supv. DATE DEC 8 1972

CONDITIONS OF APPROVAL, IF ANY: