

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-3714

<p align="center">SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</p>	
1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Coquina Oil Corporation	8. Farm or Lease Name Cities Service-State
3. Address of Operator 200 Bldg. of the Southwest, Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>E</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>26</u> TOWNSHIP <u>14-S</u> RANGE <u>34-E</u> NMPM.	10. Field and Pool, or Wildcat High Plains, Penn.
15. Elevation (Show whether DF, RT, GR, etc.) G.L. 4084	12. County Lea

<p>16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data</p>	
<p>NOTICE OF INTENTION TO:</p> <p>PERFORM REMEDIAL WORK <input type="checkbox"/></p> <p>TEMPORARILY ABANDON <input type="checkbox"/></p> <p>PULL OR ALTER CASING <input type="checkbox"/></p> <p>OTHER <input type="checkbox"/></p>	<p>SUBSEQUENT REPORT OF:</p> <p>REMEDIAL WORK <input type="checkbox"/></p> <p>COMMENCE DRILLING OPNS. <input type="checkbox"/></p> <p>CASING TEST AND CEMENT JOB <input type="checkbox"/></p> <p>OTHER <u>Spudding and casing</u> <input checked="" type="checkbox"/></p>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17 1/2" hole @ 6:00 P.M., July 24, 1973. Drilled to 380'. Cemented 34# ST&C 12 3/4" casing @ 378' with 375 sacks Class C + 2% calcium chloride. Circulated 45 sacks. Plug down @ 10:15 A.M., July 25, 1973. W.O.C. 22 hours. Drilled 11" hole to 4,550' @ 11:30 A.M., August 4, 1973. Cemented 8 5/8" 24, 28 & 32# casing @ 4,544' with 300 sacks Class C + 2% calcium chloride. W.O.C. 24 hours. Drilled out with 7 7/8" bit. Now drilling @ 6,910'. Tested BOP and 8 5/8" casing to 1000 psi for 1 hr. before drilling out. Held o.k.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNED <u>Ben D. Gould</u> (Ben D. Gould)	TITLE <u>Superintendent</u>	DATE <u>August 13, 1973</u>
APPROVED BY _____	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		