

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

<p align="center">SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" FORM C-101 FOR SUCH PROPOSALS.)</p>		<p>5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/></p>
<p>1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER</p>		<p>5. State Oil & Gas Lease No.</p>
<p>2. Name of Operator TEXAS CRUDE, INC</p>		<p>7. Unit Agreement Name</p>
<p>3. Address of Operator 2220 HNG BLDG., 1200 TRAVIS, HOUSTON, TEXAS 77002</p>		<p>8. Farm or Lease Name ALLEN</p>
<p>4. Location of Well UNIT LETTER N 2173 FEET FROM THE WEST LINE AND 467 FEET FROM THE SOUTH LINE, SECTION 17 TOWNSHIP 13-S RANGE 38-E N.M.P.M.</p>		<p>9. Well No. 1</p>
<p>15. Elevation (Show whether DF, RT, GR, etc.) 3838.3 GR</p>		<p>10. Field and Pool, or Wildcat WILDCAT</p>
<p>12. County LEA</p>		

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 6515' (154 jts.) 7" OD liner; 1500' 23#, N-80, LT&C, 2000' 26#, N-80, LT&C and 3000' 29#, N-80, LT&C. Set @ 10,775', cemented W/250 sx class H cmt. W/ 3# Gilsonite, 5# salt and 1/2# Flosele per sx. Top of cement 9860 by temp. survey, top of TIW hanger and packer 4250', bottom 9 5/8" 4610. Job complete 10:15 AM Jan 7, 1975. Tested csg. to 1500# for 15 min. Jan 9, 1975, held OK. Drilled cmt. stringer from 10,575 to LC @ 10,691. Drilled LC and plug, drilled cement from 10,691 to 10,780. Now drilling ahead.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *E. J. Littlejohn* TITLE Dist. Supt. DATE 1-10-75

APPROVED BY *Joe D. Ramsey* TITLE Dist. I, Supv. DATE 1-10-75

CONDITIONS OF APPROVAL, IF ANY: