Adobe Oil Company Adobe Oil Company Adobe Oil Company 10. Address of Operator 1100 Western United Life Bldg., Midland, Texas 79701 10. Fleed and Phol, or Wildon Drides of Company 110. Fleed and Phol, or Wildon Drides of Company 127 Township 13-8 RANGE Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Subsequent Report of: Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Subsequent Report of: Check Appropriate Subsequent Report or Other Subsequent Report of: Check Appropriate Subsequent Report of: Check Appropriate Subsequent Report of Check Subsequent Report of: Check Appropriate Subsequent Report of Check S	NEW MEXICO OIL CONSERVATION COMMISSION Construction of the Constr	NO. OF COPIES RECEIVED				Form C-1	
NEW MEXICO OIL CONSERVATION COMMISSION FILE U.S.O.S. South discrete Type of Lease State Free Ex. South Deferring Type of Lease State Free Ex. South Deferring Type of Lease State South Deferring Type of Lease State Free Ex. South Deferring Type of Lease Free Ex. South Deferrin	NEW MEXICO OIL CONSERVATION COMMISSION PRICE U.S.O.S. Souther Type of Leave State Of Leave Type of Leave Adobe Off Company 1. More State Of Leave Type of Leave Adobe Off Company 2. More State Of Leave Type of Leave State Of Leave Type of Leave State Off Leave Type of Leave Type of Leave State Off Leave Type of Leave Type of Leave State Off Leave Type of Leave Type		 				
USAGO. S. SUNDRY NOTICES AND REPORTS ON WELLS S. SUND OF JUST PRINTED BY A STANDARD OF THE ST	So. Indicate Type of Long State		NEW	MEXICO OIL CONS	ERVATION COMMISSION		
State Out & Gas Leave No. State Out & Gas Leave No.	SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS STATES. SUNDRY NOTICES AND REPORTS ON WELLS STATES. SUNDRY NOTICES AND REPORTS ON WELLS STATES. THE SET OF STATES. Adobe 011 Company Adobe 011 Company Sundry The Sundry Align Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: Sundry Su		+			<u> </u>	
SUNDRY NOTICES AND REPORTS ON WELLS OR NOT USE THE FORWARD PROPERTY OF THE PROPERTY OF SHEW PROPERTY ASSOCIATION FOR MAINT. TO INCREME THE PROPERTY OF THE PR	SUNDRY NOTICES AND REPORTS ON WELLS SUNDRY NOTICES AND REPORTS ON WELLS POWER OF THE PROPERTY OF THE PROPERTY SOLD PROPERTY SOLD WELLS POWER OF COMPANY Adobe Oil		+				·
SUNDRY NOTICES AND REPORTS ON WELLS "THE STATE CONTROL OF THE PRODUCT OF THE PRO	SUNDRY NOTICES AND REPORTS ON WELLS OF THE PROPERTY OF THE PR		+-1				
Adobe Oil Company A bell No. 10. Feeld and Pool, or Wildcel Dudge innated ALE NOT COMPANY ALE NOT COM	Address of Operators Adobe Oil Company 3. Address of Operators Adobe Oil Company 3. Address of Operators 1100 Western United Life Bldg., Midland, Texas 79701 5. Location of well Out Letter G 1980 PERT FROM THE NOTE 13-8 AANE 1780 TEXT FROM 18. Elevation (Show whether DF, RT, GR, atc.) Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: PLUS AND ARABODON THAPPRANEITY ARABOD THAPPARABOD THAPPRANEITY ARABOD THAPPARABOD THAPPARABOD THAPPARAB	OPERATOR				5. State Oil 6	Gas Lease No.
Adobe Oil Company A bell No. 10. Feeld and Pool, or Wildcel Dudge innated ALE NOT COMPANY ALE NOT COM	Address of Operators Adobe Oil Company 3. Address of Operators Adobe Oil Company 3. Address of Operators 1100 Western United Life Bldg., Midland, Texas 79701 5. Location of well Out Letter G 1980 PERT FROM THE NOTE 13-8 AANE 1780 TEXT FROM 18. Elevation (Show whether DF, RT, GR, atc.) Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: PLUS AND ARABODON THAPPRANEITY ARABOD THAPPARABOD THAPPRANEITY ARABOD THAPPARABOD THAPPARABOD THAPPARAB	<u> </u>	NDBY NOTICES	ID DEDOD-0 6		mm/	mmm
Adobe Oil Company Adobe Oil Company 1. Address of Operator 1100 Western United Life Bidg., Midland, Texas 79701 1. Location of Well ONLY CETTER G 1980 TOWNSHIP LINE AND THE LINE AND TEST FROM THE LINE AND T	Adobe 011 Company Adobe 011 Company 1. Address of Operation 1. Address of Operation Operations of Oper	(DO NOT USE THIS FORM FO	NUKY NUTICES AND PROPOSALS TO DRILL OF PERMIT -"	NU KEPURTS ON R TO DEEPEN OR PLUG E (FORM C-101) FOR SUC	WELLS ACK TO A DIFFERENT RESERVOIR. H PROPOSALS.)		
Adobe 011 Company 1. Addiess of Operator 1100 Western United Life Bldg., Midland, Texas 79701 1. Location of Well 1. Location of We	Address of Operator 1. Operator	OIL GAS	OTHER-			7. Unit Agree	ment Name
1. Address of Operator 1100 Western United Life Bidg., Midland, Texas 79701 1. Location of Well Unit Letter G 1980 rect from the north line Ano 34-E	11.00 Western United Life Bldg., Midland, Texas 79701 1. Location of West 1. Location of We	2. Name of Operator				8. Form or Le	ease Name
1100 Western United Life Bldg., Midland, Texas 79701 1. Location of Weil Only Cetter Completed Operation (Show whether DF, RT, CR, etc.) 13-8 **RANGE** Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: **REMEDIAL WORK** CHANGE PLANS CHANGE PLANS COMMERCE BRILLING DPMS.** TEMPORARILY ABANDON OTHER 7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting ony propose work) SEE RULE 1703. Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50f casing and set at 428'. Commence of Notice of Notice in the Complete Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting ony propose work) SEE RULE 1703. Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50f casing and set at 428'. Commence of the Complete Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting ony propose work) SEE RULE 1703. Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50f casing and set at 428'. Commence of the Complete Com	1100 Western United Life Bldg., Midland, Texas 79701 1		mpany				8
The cast Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose or the table to 10,005°. Took 10" preflow and open with weak blow and increased to strong blow, GTS in 60°, flowing pressure 18-218° from 10,367°. Took 10" preflow and open with weak blow increased to fair blow, recovered no pressure because packer 311pg d. 96° (Clearly state of the beat of my knowledge and belief.	13-8 13-8 14-18 15-18-19-19-19-19-19-19-19-19-19-19-19-19-19-	·				9. Well No.	
THE CASING TEMPORAL PLANS OF THE TROOM THE CASING THE PARKET PROPERTY AND SECURITY	THE CASE THE PROPERTY OF THE P		United Life Bl	dg., Midland,	Texas 79701		
The east the first state of the	13-S 34-E NAME OF THE SECTION 27 TOWNSHIP 13-S ARGE NAME OF STATE		1980	nowth	1780		
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS ALTERING CASING ALTERING CASING CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS ALTERING CASING ALTERING CASING CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CASING TEST AND CLUME PLANS CASING TEST AND	Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PILL OR ALTERIAC CASING CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS CHANGE PLANS COMMENCE ORILLING ORB. CASING COMMENCE ORILLING ORB. CASING CEMENT JOB PULL OR ALTER CASING CHANGE PLANS COMMENCE ORILLING ORB. CASING TOWARD ADARDOM PULL OR ALTER CASING CHANGE PLANS COMMENCE ORILLING ORB. CASING TOWARD ADARDOM PULL OR ALTER CASING COMMENCE ORILLING ORB. CASING TOWARD ADARDOM PULL OR ALTER CASING COMMENCE ORILLING ORB. CASING TOWARD ADARDOM PULL OR ALTER CASING COMMENCE ORILLING ORB. CASING TOWARD ADARDOM PULL OR ALTER CASING COMMENCE ORILLING ORB. CASING TOWARD ADARDOM PULL OR ALTER CASING COMMENCE ORILLING ORB. PLUS AND ABANDOMHENT CASING TOWARD ADARDOM PULL OR ALTER CASING COMMENCE ORILLING ORB. PLUS AND ABANDOMHENT CASING TOWARD ADARDOM PULL OR ALTER CASING COMMENCE ORILLING ORB. PLUS AND ABANDOMHENT CASING TOWARD ADARDOM PULL OR ALTER CASING COMMENCE ORILLING ORB. PLUS AND ABANDOMHENT CASING TOWARD ADARDOM PULL OR ALTER CASING COMMENCE ORILLING ORB. ALTERING CASING COMMENCE ORILLING ORB. PLUS AND ABANDOMHENT CASING TOWARD ADARDOM ALTERING CASING COMMENCE ORILLING ORB. ALTERING CASING COMMENCE ORILLING ORB. PLUS AND ABANDOMHENT CASING TOWARD ADARDOM ALTERING CASING COMMENCE ORILLING ORB. ALTERING CASING COMMENCE ORILLING COMMENCE ORILLING COMMENCE ORILLING COMMENCE ORILLING ALTER CASING COMMENCE ORIL	UNIT LETTER,	FEET FR	OM THE	LINE AND FEE	T FROM	Undesignated
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: REMEDIAL WORK PULL AND ABANDON CHANGE PLANS CALLERING CASING TOWARD CHANGE PLANS CHANGE PLANS CALLERING CASING ALTERING CASING ALTERING CASING ALTERING CASING TOWARD CHANGE PLANS CASING TEST AND CHANGE PLANS CASING THE TATALL MORE ALTERING CASING ALTE	Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PREMORABLY ABANDON PULL OR ALTER CASING CHANGE PLANS COMMENCE DRILLING DRIS. COMMENCE DRILLING DRIS. CHANGE PLANS COMMENCE DRILLING DRIS. CHANGE PLANS COMMENCE DRILLING DRIS. CASING TEST AND CEMERY JOB OTHER COMMENCE DRILLING DRIS. CHANGE PLANS CH	THELINE, S	27	_ TOWNSHIP	34-E	NMPM.	
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PRIFORM REMEDIAL WORK TEMPORABILY ABANDON PULIC AND ABANDON THEMPORABILY ABANDON OTHER OTHER TO DESCRIBE Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose work) SEE RULE 1103. Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50# casing and set at 428'. Cemented w/400 sxs class "C" w/2% CaCl. Cement circulated. Pressure tested casing to 1000# for 8 hrs - held ok. Drilled to 4312' and ran 8-5/8" 24#, 28#, 32# casing and set at 4312'. Cemented with 200 sxs class "H" 4% gel, 5# salt/sx plus 100 sxs class "B" w/2% CaCl. Pressure tested casing to 1500# for 8 hours and held ok. Drilled to 10,005' and ran BST #1 from 9974 to 10,005'. Took 10" preflow and open with weak blow. FP 94-117#, took 30" ISI w/3344#, took 30" FF w/no blow, FP 94-140#, took 60" FSI w/3205#, I hyd 4495, F hyd 4453. Recovered 210' drilling mud. Drilled to 10,367' and DST #2 from 10,350' to 10,367'. Took 10" preflow and open with weak blow increased to fair blow, recovered no pressures because packer slipped, took 45" ISI w/2296# SIP, took 1 hour flow - opened with weak blow and increased to strong blow, GTS in 60", flowing pressure 128-218#. Took 190" FSI with pressure of 2211#. Recovered 480' oil above circulating sub and 120' HO&6CCM below circulator sub. Drilled to 10,500'. Cemented with 100 sxs litewate w/15# salt/sx plus 400 sxs class "C" 50/50 pozmir, 2% gel, 6# salt/sx and 1/4# flocele/sx and 1% CFR2. POB 6:30 pm 2/20/75. Pressure tested casing to 3000# for 8 hrs - held ok. Now waiting on rig to move.	Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL ON ALTER CASING OTHER THANGE PLANS CHANGE PLANS COMMENCE OPHILLING OPHS. CHANGE PLANS ALTERING CASING ACTEMING AND ABANDONIME CHANGE PLANS CH				DF, RT, GR, etc.)		•••
PERFORM REMEDIAL WORK TEMPORARILY ABANDON THE PLUS AND ABANDON THE PLUS AND ABANDON CHANGE PLANS COMMENCE DRILLING CARING CHANGE PLANS CASING TEST AND CEMENT JUB	PERFORM REMEDIAL WORK PLUE AND ABANDON OTHER OTH	16.	ok Appendiese Pe	T- I-1:	CN C		
PLUS AND ABANDON THEMPORARILY THEMPORARILY ABANDON THEMPORARILY THEMPORARILY ABANDON THEMPORARILY THEMPORARILY ABANDON THEMPORARILY TH	PLUG AND ABANDON PLUG AND ABANDONMENT PLUG						NE.
PLUG AND ABANDON PULL ON ALTER CASING CHANGE PLANS CHANGE PLANS CHANGE PLANS COMMENCE DRILLING OPHS. 7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose work) SEE RULE 1703. Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50\(\frac{1}{2} \) casing and set at 428'. Cemented w/400 sxs class "C" w/2X CaCl. Cement circulated. Pressure tested casing to 1000\(\frac{1}{2} \) for 8 hrs - held ok. Drilled to 4312' and ran 8-5/8" 24\(\frac{1}{2} \) 28\(\frac{1}{2} \) 28\(\frac{1}{2} \) casing and set at 4312'. Cemented with 200 sxs class "H" 4X gel, 5\(\frac{1}{2} \) sat 1/sx plus 100 sxs class "H" w/2X CaCl. Pressure tested casing to 1500\(\frac{1}{2} \) for 8 hours and held ok. Drilled to 10,005' and ran DST \(\frac{1}{2} \) from 9974 to 10,005'. Took 10" preflow and open with weak blow. FP 94-117\(\frac{1}{2} \), took 3\(\frac{1}{2} \) in 3344\(\frac{1}{2} \), took 30" FF w/no blow, FP 94-140\(\frac{1}{2} \), took 60" FSI w/3205\(\frac{1}{2} \), 1 hyd 4495, F hyd 4453. Recovered 210' drilling mud. Drilled to 10,367' and DST \(\frac{1}{2} \) from 10,350' to 10,367'. Took 10" preflow and open with weak blow increased to fair blow, recovered no pressures because packer slipped, took 45" ISI w/2296\(\frac{1}{2} \) SIP, took 1 hour flow - opened with weak blow and increased to strong blow, GTS in 60", flowing pressure 128-218\(\frac{1}{2} \). Took 190" FSI with pressure of 2211\(\frac{1}{2} \). Recovered 480' oil above circulating sub and 120' H066GM below circulator sub. Drilled to 10,500' lime and ran open-hole logs. Ran 5-1/2" 17\(\frac{1}{2} \) 20\(\frac{1}{2} \) casing and set at 10,500'. Cemented with 100 sxs litewate w/15\(\frac{1}{2} \) salt/sx plus 400 sxs class "C" 50/50 pozmix, 2\(\frac{1}{2} \) gel, 6\(\frac{1}{2} \) salt/sx and 1/4\(\frac{1}{2} \) flocele/sx and 1\(\frac{1}{2} \) flocele/sx and 1\(\frac{1}{2} \) flocele/sx and belief.	COMMERCE ORIGING OPENS. CASING TEST AND CEMENT JOB OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose work) SEE ROLE 1703. Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50f casing and set at 428'. Cemented w/400 sxs class "C" w/2X CaCl. Cement circulated. Pressure tested casing to 1000f for 8 hrs - held ok. Drilled to 4312' and ran 8-5/8" 24f, 28f, 32f casing and set at 4312'. Cemented with 200 sxs class "H" 4X gel, 5f salt/sx plus 100 sxs class "H" w/2X CaCl. Pressure tested casing to 1500f for 8 hours and held ok. Drilled to 10,005' and ran DST fl from 9974 to 10,005'. Took 10" preflow and open with weak blow. FF 94-117f, took 60" FSI w/3344f, took 30" FF w/no blow, FF 94-140f, took 60" FSI w/3205f, I hyd 4495, F hyd 4453. Recovered 210' drilling mud. Drilled to 10,367' and DST fl from 10,350' to 10,367'. Took 10" preflow and open with weak blow increased to fair blow, recovered no pressures because packer slipped, took 45" ISI w/2296f SIP, took 1 hour flow - opened with weak blow and increased to strong blow, GTS in 60", flowing pressure 128-218f. Took 190" FSI with pressure of 2211f. Recovered 480' oil above circulating sub and 120' HOGGCM below circulator sub. Drilled to 10,500' lime and ran open-hole logs. Ran 5-1/2" 17f & 20f casing and set at 10,500'. Cemented with 100 sxs litewate w/15f salt/sx plus 400 sxs class "C" 50/50 pozmix, 2X gel, 6f salt/sx and 1/4f flocele/sx and 1X CFR2. POB 6:30 pm 2/20/75. Pressure tested casing to 3000f for 8 hrs - held ok. Now waiting on rig to move. **Index Vice President** **Vice President**	NOTICE	A THE ENTION TO:		SUBSEQ	UENI REPORT C) - :
PLUG AND ABANDON PULL ON ALTER CASING CHANGE PLANS CHANGE PLANS CHANGE PLANS COMMENCE DRILLING OPHS. 7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose work) SEE RULE 1703. Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50\(\frac{1}{2} \) casing and set at 428'. Cemented w/400 sxs class "C" w/2X CaCl. Cement circulated. Pressure tested casing to 1000\(\frac{1}{2} \) for 8 hrs - held ok. Drilled to 4312' and ran 8-5/8" 24\(\frac{1}{2} \) 28\(\frac{1}{2} \) 28\(\frac{1}{2} \) casing and set at 4312'. Cemented with 200 sxs class "H" 4X gel, 5\(\frac{1}{2} \) sat 1/sx plus 100 sxs class "H" w/2X CaCl. Pressure tested casing to 1500\(\frac{1}{2} \) for 8 hours and held ok. Drilled to 10,005' and ran DST \(\frac{1}{2} \) from 9974 to 10,005'. Took 10" preflow and open with weak blow. FP 94-117\(\frac{1}{2} \), took 3\(\frac{1}{2} \) in 3344\(\frac{1}{2} \), took 30" FF w/no blow, FP 94-140\(\frac{1}{2} \), took 60" FSI w/3205\(\frac{1}{2} \), 1 hyd 4495, F hyd 4453. Recovered 210' drilling mud. Drilled to 10,367' and DST \(\frac{1}{2} \) from 10,350' to 10,367'. Took 10" preflow and open with weak blow increased to fair blow, recovered no pressures because packer slipped, took 45" ISI w/2296\(\frac{1}{2} \) SIP, took 1 hour flow - opened with weak blow and increased to strong blow, GTS in 60", flowing pressure 128-218\(\frac{1}{2} \). Took 190" FSI with pressure of 2211\(\frac{1}{2} \). Recovered 480' oil above circulating sub and 120' H066GM below circulator sub. Drilled to 10,500' lime and ran open-hole logs. Ran 5-1/2" 17\(\frac{1}{2} \) 20\(\frac{1}{2} \) casing and set at 10,500'. Cemented with 100 sxs litewate w/15\(\frac{1}{2} \) salt/sx plus 400 sxs class "C" 50/50 pozmix, 2\(\frac{1}{2} \) gel, 6\(\frac{1}{2} \) salt/sx and 1/4\(\frac{1}{2} \) flocele/sx and 1\(\frac{1}{2} \) flocele/sx and 1\(\frac{1}{2} \) flocele/sx and belief.	COMMERCE ORIGING OPENS. CASING TEST AND CEMENT JOB OTHER 17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose work) SEE ROLE 1703. Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50f casing and set at 428'. Cemented w/400 sxs class "C" w/2X CaCl. Cement circulated. Pressure tested casing to 1000f for 8 hrs - held ok. Drilled to 4312' and ran 8-5/8" 24f, 28f, 32f casing and set at 4312'. Cemented with 200 sxs class "H" 4X gel, 5f salt/sx plus 100 sxs class "H" w/2X CaCl. Pressure tested casing to 1500f for 8 hours and held ok. Drilled to 10,005' and ran DST fl from 9974 to 10,005'. Took 10" preflow and open with weak blow. FF 94-117f, took 60" FSI w/3344f, took 30" FF w/no blow, FF 94-140f, took 60" FSI w/3205f, I hyd 4495, F hyd 4453. Recovered 210' drilling mud. Drilled to 10,367' and DST fl from 10,350' to 10,367'. Took 10" preflow and open with weak blow increased to fair blow, recovered no pressures because packer slipped, took 45" ISI w/2296f SIP, took 1 hour flow - opened with weak blow and increased to strong blow, GTS in 60", flowing pressure 128-218f. Took 190" FSI with pressure of 2211f. Recovered 480' oil above circulating sub and 120' HOGGCM below circulator sub. Drilled to 10,500' lime and ran open-hole logs. Ran 5-1/2" 17f & 20f casing and set at 10,500'. Cemented with 100 sxs litewate w/15f salt/sx plus 400 sxs class "C" 50/50 pozmix, 2X gel, 6f salt/sx and 1/4f flocele/sx and 1X CFR2. POB 6:30 pm 2/20/75. Pressure tested casing to 3000f for 8 hrs - held ok. Now waiting on rig to move. **Index Vice President** **Vice President**	PERFORM REMEDIAL WORK	PI	UG AND ABANDON	REMEDIAL WORK	٦	TERING CASING
OTHER CHANGE PLANS CASING TEST AND CEMENT JOB OTHER CASING TEST AND CEMENT JOB OTHER CASING TEST AND CEMENT JOB OTHER 7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose work) SEE RULE 1103. Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50# casing and set at 428'. Cemented w/400 sxs class "C" w/2X CaCl. Cement circulated. Pressure tested casing to 1000# for 8 hrs - held ok. Drilled to 4312' and ran 8-5/8" 24#, 28#, 32# casing and set at 4312'. Cemented with 200 sxs class "H" 4X gel, 5# salt/sx plus 100 sxs class "H" w/2X CaCl. Pressure tested casing to 1500# for 8 hours and held ok. Drilled to 10,005' and ran DST #1 from 9974 to 10,005'. Took 10" preflow and open with weak blow. FP 94-117#, took 30" ISI w/3344#, took 30" FF w/no blow, FP 94-140#, took 60" FSI w/3205#, I hyd 4495, F hyd 4453. Recovered 210' drilling mud. Drilled to 10,367' and DST #2 from 10,350' to 10,367'. Took 10" preflow and open with weak blow increased to fair blow, recovered no pressures because packer slipped, took 45" ISI w/2296# SIP, took 1 hour flow - opened with weak blow and increased to strong blow, GTS in 60", flowing pressure 128-218#. Took 190" FSI with pressure of 2211#. Recovered 480' oil above circulating sub and 120' Ho&GCM below circulator sub. Drilled to 10,500' lime and ran open-hole logs. Ran 5-1/2" 17# & 20# casing and set at 10,500'. Cemented with 100 sxs litewate w/15# salt/sx plus 400 sxs class "C" 50/50 pozmix, 2% gel, 6# salt/sx and 1/4# flocele/sx and 1% CFR2. POB 6:30 pm 2/20/75. Pressure tested casing to 3000# for 8 hrs - held ok. Now waiting on rig to move. 8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	CHANGE PLANS CASING TEST AND CEMENT JQB OTHER 7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose work) SEE ROLE 1193. Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50# casing and set at 428'. Cemented w/400 sxs class "C" w/2X CaCl. Cement circulated. Pressure tested casing to 1000# for 8 hrs - held ok. Drilled to 4312' and ran 8-5/8" 24#, 28#, 32# casing and set at 4312'. Cemented with 200 sxs class "H" 4X gel, 5# salt/sx plus 100 sxs class "H" 4X yel, 5# salt/sx plus 100 sxs class "H" 4X yel, 5# salt/sx plus 100 sxs class "H" 4X yel, 5# salt/sx plus 100 sxs class "H" 4X yel, 5# yell yell yell yell yell yell yell yel	=	P.		-	≒	· -
7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose work) SEE RULE 1703. Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50# casing and set at 428'. Cemented w/400 sxs class "C" w/2X CaCl. Cement circulated. Pressure tested casing to 1000# for 8 hrs - held ok. Drilled to 4312' and ran 8-5/8" 24#, 28#, 32# casing and set at 4312'. Cemented with 200 sxs class "H" 4X gel, 5# salt/sx plus 100 sxs class "H" w/2X CaCl. Pressure tested casing to 1500# for 8 hours and held ok. Drilled to 10,005' and ran DST #1 from 9974 to 10,005'. Took 10" preflow and open with weak blow. FP 94-117#, took 30" ISI w/3344#, took 30" FF w/no blow, FP 94-140#, took 60" FSI w/3205#, I hyd 4495, F hyd 4453. Recovered 210' drilling mud. Drilled to 10,367' and DST #2 from 10,350' to 10,367'. Took 10" preflow and open with weak blow increased to fair blow, recovered no pressures because packer slipped, took 45" ISI w/2296# SIP, took 1 hour flow - opened with weak blow and increased to strong blow, GTS in 60", flowing pressure 128-218#. Took 190" FSI with pressure of 2211#. Recovered 480' oil above circulating sub and 120' H0&GCM below circulator sub. Drilled to 10,500' lime and ran open-hole logs. Ran 5-1/2" 17# & 20# casing and set at 10,500'. Cemented with 100 sxs litewate w/15# salt/sx plus 400 sxs class "C" 50/50 pozmix, 2% gel, 6# salt/sx and 1/4# flocale/sx and 1% CFR2. POB 6:30 pm 2/20/75. Pressure tested casing to 3000# for 8 hrs - held ok. Now waiting on rig to move.	7. Describe Proposed or Completed Operations (Clearly state all persinent details, and give persinent dates, including estimated date of starting any propose work) SEE ROLE 1703. Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50# casing and set at 428'. Cemented w/400 sxs class "C" w/2X CaCl. Cement circulated. Pressure tested casing to 1000# for 8 hrs - held ok. Drilled to 4312' and ran 8-5/8" 24#, 28#, 32# casing and set at 4312'. Cemented with 200 sxs class "H" 4X gel, 5# salt/sx plus 100 sxs class "H" w/2X CaCl. Pressure tested casing to 1500# for 8 hours and held ok. Drilled to 10,005' and ran DST #1 from 9974 to 10,005'. Took 10" preflow and open with weak blow. FP 94-117#, took 39" ISI w/3344#, took 30" FF w/no blow, FP 94-140#, took 60" FSI w/3205#, I hyd 4495, F hyd 4453. Recovered 210' drilling mud. Drilled to 10,367' and DST #2 from 10,350' to 10,367'. Took 10" preflow and open with weak blow increased to fair blow, recovered no pressures because packer slipped, took 45" ISI w/2296# SIP, took 1 hour flow - opened with weak blow and increased to strong blow, GTS in 60", flowing pressure 128-218#. Took 190" FSI with pressure of 2211#. Recovered 480' oil above circulating sub and 120' H06GCM below circulator sub. Drilled to 10,500' lime and ran open-hole logs. Ran 5-1/2" 17# & 20# casing and set at 10,500'. Cemented with 100 sxs litewate w/15# salt/sx plus 400 sxs class "C" 50/50 pozmix, 2X gel, 6# salt/sx and 1/4# flocele/sx and 1% CFR2. POB 6:30 pm 2/20/75. Pressure tested casing to 3000# for 8 hrs - held ok. Now waiting on rig to move. **Note: Vice President	=	CH	IANGE PLANS	198	=	AND ABANDUNMENT
7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose work) SEE RULE 1103. Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50# casing and set at 428'. Cemented w/400 sxs class "C" w/2% CaCl. Cement circulated. Pressure tested casing to 1000# for 8 hrs - held ok. Drilled to 4312' and ran 8-5/8" 24#, 28#, 32# casing and set at 4312'. Cemented with 200 sxs class "H" 4% gel, 5# salt/sx plus 100 sxs class "H" w/2% CaCl. Pressure tested casing to 1500# for 8 hours and held ok. Drilled to 10,005' and ran DST #1 from 9974 to 10,005'. Took 10" preflow and open with weak blow. FF 94-117#, took 30" ISI w/3344#, took 30" FF w/no blow, FF 94-140#, took 60" FSI w/3205#, I hyd 4495, F hyd 4453. Recovered 210' drilling mud. Drilled to 10,367' and DST #2 from 10,350' to 10,367'. Took 10" preflow and open with weak blow increased to fair blow, recovered no pressures because packer slipped, took 45" ISI w/2296# SIP, took 1 hour flow - opened with weak blow and increased to strong blow, GTS in 60", flowing pressure 128-218#. Took 190" FSI with pressure of 2211#. Recovered 480' oil above circulating sub and 120' H06GCM below circulator sub. Drilled to 10,500' lime and ran open-hole logs. Ran 5-1/2" 17# & 20# casing and set at 10,500'. Cemented with 100 sxs litewate w/15# salt/sx plus 400 sxs class "C" 50/50 pozmix, 2% gel, 6# salt/sx and 1/4# flocele/sx and 1% CFR2. POB 6:30 pm 2/20/75. Pressure tested casing to 3000# for 8 hrs - held ok. Now waiting on rig to move.	7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any propose work) SEE RULE 1703. Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50# casing and set at 428'. Cemented w/400 sxs class "C" w/2% CaCl. Cement circulated. Pressure tested casing to 1000# for 8 hrs - held ok. Drilled to 4312' and ran 8-5/8" 24#, 28#, 32#, 32# casing and set at 4312'. Cemented with 200 sxs class "H" 4% gel, 5# salt/sx plus 100 sxs class "H" w/2% CaCl. Pressure tested casing to 1500# for 8 hours and held ok. Drilled to 10,005' and ran DST #1 from 9974 to 10,005'. Took 10" preflow and open with weak blow. FP 94-117#, took 39" ISI w/3344#, took 30" FF w/no blow, FP 94-140#, took 60" FSI w/3205#, I hyd 4495, F hyd 4453. Recovered 210' drilling mud. Drilled to 10,367' and DST #2 from 10,350' to 10,367'. Took 10" preflow and open with weak blow increased to fair blow, recovered no pressures because packer slipped, took 45" ISI w/2296# SIP, took 1 hour flow - opened with weak blow and increased to strong blow, GTS in 60", flowing pressure 128-218#. Took 190" FSI with pressure of 2211#. Recovered 480' oil above circulating sub and 120' H0&GCM below circulator sub. Drilled to 10,500' lime and ran open-hole logs. Ran 5-1/2" 17# & 20# casing and set at 10,500'. Cemented with 100 sxs litewate w/15# salt/sx plus 400 sxs class "C" 50/50 pozmix, 2% gel, 6# salt/sx and 1/4# flocele/sx and 1% CFR2. POB 6:30 pm 2/20/75. Pressure tested casing to 3000# for 8 hrs - held ok. Now waiting on rig to move. **ITTLE Vice President**				_		
Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50# casing and set at 428'. Camented w/400 sxs class "C" w/2% CaCl. Cement circulated. Pressure tested casing to 1000# for 8 hrs - held ok. Drilled to 4312' and ran 8-5/8" 24#, 28#, 32# casing and set at 4312'. Cemented with 200 sxs class "H" 4% gel, 5# salt/sx plus 100 sxs class "H" w/2% CaCl. Pressure tested casing to 1500# for 8 hours and held ok. Drilled to 10,005' and ran DST #1 from 9974 to 10,005'. Took 10" preflow and open with weak blow. FP 94-117#, took 39" ISI w/3344#, took 30" FF w/no blow, FP 94-140#, took 60" FSI w/3205#, I hyd 4495, F hyd 4453. Recovered 210' drilling mud. Drilled to 10,367' and DST #2 from 10,350' to 10,367'. Took 10" preflow and open with weak blow increased to fair blow, recovered no pressures because packer slipped, took 45" ISI w/2296# SIP, took 1 hour flow - opened with weak blow and increased to strong blow, GTS in 60", flowing pressure 128-218#. Took 190" FSI with pressure of 2211#. Recovered 480' oil above circulating sub and 120' HO&GCM below circulator sub. Drilled to 10,500' lime and ran open-hole logs. Ran 5-1/2" 17# & 20# casing and set at 10,500'. Cemented with 100 sxs litewate w/15# salt/sx plus 400 sxs class "C" 50/50 pozmix, 2% gel, 6# salt/sx and 1/4# flocele/sx and 1% CFR2. POB 6:30 pm 2/20/75. Pressure tested casing to 3000# for 8 hrs - held ok. Now waiting on rig to move.	Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50# casing and set at 428'. Cemented w/400 sxs class "C" w/2% CaCl. Cement circulated. Pressure tested casing to 1000# for 8 hrs - held ok. Drilled to 4312' and ran 8-5/8" 24#, 28#, 32# casing and set at 4312'. Cemented with 200 sxs class "H" 4% gel, 5# salt/sx plus 100 sxs class "H" w/2% CaCl. Pressure tested casing to 1500# for 8 hours and held ok. Drilled to 10,005' and ran DST #1 from 9974 to 10,005'. Took 10" preflow and open with weak blow. FF 94-117#, took 39" ISI w/3344#, took 30" FF w/no blow, FF 94-140#, took 60" FSI w/3205#, I hyd 4495, F hyd 4453. Recovered 210' drilling mud. Drilled to 10,367' and DST #2 from 10,350' to 10,367'. Took 10" preflow and open with weak blow increased to fair blow, recovered no pressures because packer slipped, took 45" ISI w/2296# SIP, took 1 hour flow - opened with weak blow and increased to strong blow, GTS in 60", flowing pressure 128-218#. Took 190" FSI with pressure of 2211#. Recovered 480' oil above circulating sub and 120' HO&GCM below circulator sub. Drilled to 10,500' lime and ran open-hole logs. Ran 5-1/2" 17# & 20# casing and set at 10,500'. Cemented with 100 sxs litewate w/15# salt/sx plus 400 sxs class "C" 50/50 pozmix, 2% gel, 6# salt/sx and 1/4# flocele/sx and 1% CFR2. POB 6:30 pm 2/20/75. Pressure tested casing to 3000# for 8 hrs - held ok. Now waiting on rig to move. 8.1 hereby certify that the information above is true and complete to the best of my knowledge and belief.	OTHER					
Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50# casing and set at 428'. Camented w/400 sxs class "C" w/2% CaCl. Cement circulated. Pressure tested casing to 1000# for 8 hrs - held ok. Drilled to 4312' and ran 8-5/8" 24#, 28#, 32# casing and set at 4312'. Cemented with 200 sxs class "H" 4% gel, 5# salt/sx plus 100 sxs class "H" w/2% CaCl. Pressure tested casing to 1500# for 8 hours and held ok. Drilled to 10,005' and ran DST #1 from 9974 to 10,005'. Took 10" preflow and open with weak blow. FP 94-117#, took 39" ISI w/3344#, took 30" FF w/no blow, FP 94-140#, took 60" FSI w/3205#, I hyd 4495, F hyd 4453. Recovered 210' drilling mud. Drilled to 10,367' and DST #2 from 10,350' to 10,367'. Took 10" preflow and open with weak blow increased to fair blow, recovered no pressures because packer slipped, took 45" ISI w/2296# SIP, took 1 hour flow - opened with weak blow and increased to strong blow, GTS in 60", flowing pressure 128-218#. Took 190" FSI with pressure of 2211#. Recovered 480' oil above circulating sub and 120' HO&GCM below circulator sub. Drilled to 10,500' lime and ran open-hole logs. Ran 5-1/2" 17# & 20# casing and set at 10,500'. Cemented with 100 sxs litewate w/15# salt/sx plus 400 sxs class "C" 50/50 pozmix, 2% gel, 6# salt/sx and 1/4# flocele/sx and 1% CFR2. POB 6:30 pm 2/20/75. Pressure tested casing to 3000# for 8 hrs - held ok. Now waiting on rig to move.	Spudded well 1/22/75 and drilled to 435' redbeds. Ran 11 jts 13-3/8" 54.50# casing and set at 428'. Cemented w/400 sxs class "C" w/2% CaCl. Cement circulated. Pressure tested casing to 1000# for 8 hrs - held ok. Drilled to 4312' and ran 8-5/8" 24#, 28#, 32# casing and set at 4312'. Cemented with 200 sxs class "H" 4% gel, 5# salt/sx plus 100 sxs class "H" w/2% CaCl. Pressure tested casing to 1500# for 8 hours and held ok. Drilled to 10,005' and ran DST #1 from 9974 to 10,005'. Took 10" preflow and open with weak blow. FF 94-117#, took 39" ISI w/3344#, took 30" FF w/no blow, FF 94-140#, took 60" FSI w/3205#, I hyd 4495, F hyd 4453. Recovered 210' drilling mud. Drilled to 10,367' and DST #2 from 10,350' to 10,367'. Took 10" preflow and open with weak blow increased to fair blow, recovered no pressures because packer slipped, took 45" ISI w/2296# SIP, took 1 hour flow - opened with weak blow and increased to strong blow, GTS in 60", flowing pressure 128-218#. Took 190" FSI with pressure of 2211#. Recovered 480' oil above circulating sub and 120' HO&GCM below circulator sub. Drilled to 10,500' lime and ran open-hole logs. Ran 5-1/2" 17# & 20# casing and set at 10,500'. Cemented with 100 sxs litewate w/15# salt/sx plus 400 sxs class "C" 50/50 pozmix, 2% gel, 6# salt/sx and 1/4# flocele/sx and 1% CFR2. POB 6:30 pm 2/20/75. Pressure tested casing to 3000# for 8 hrs - held ok. Now waiting on rig to move. 8.1 hereby certify that the information above is true and complete to the best of my knowledge and belief.						
	IGNED M. 4 Gy TITLE Vice President DATE 2/25/75	set at 428'. Cement casing to 1000# for and set at 4312'. Of the work of the w	sed w/400 sxs c 8 hrs - held of Cemented with 2 sure tested ca 9974 to 10,005 f, took 30" FF red 210' drilling oreflow and open taker slipped, ased to strong 5 2211f. Recover 111ed to 10,500 Cemented with	class "C" w/22 class "C" w/22 class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class class clas	CaCl. Cement circle of 4312' and ran 8-5. "H" 4% gel, 5# salt, for 8 hours and help preflow and open with 94-140#, took 60" led to 10,367' and lolow increased to fair w/2296# SIP, took 1 60", flowing pressure above circulating an open-hole logs. I wate w/15# salt/sx pale/sx and 1% CFR2.	ulated. Press /8" 24#, 28#, /sx plus 100 s 1d ok. Drille th weak blow. FSI w/3205#, : DST #2 from 10 ir blow, recompour flow - 0 re 128-218#. sub and 120' 1 Ran 5-1/2" 17: plus 400 sxs of POB 6:30 pm :	sure tested 32# casing sxs class ed to 10,005' FP 94-117#, I hyd 4495, 0,350' to vered no opened with Took 190" HO&GCM below # & 20# casing class "C" 2/20/75.
IGNED							.
		IGNED M. H.	6:4-	TITLE \$	ice President	DATE	2/25/75
						- Polit	

CONDITIONS OF APPROVAL, IF ANY:

Last. J. Sugar,