

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-B1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	5. LEASE, DEED, EASEMENT, AND SERIAL NO. NM-19213-A
2. NAME OF OPERATOR Tom L. Ingram	6. IF INDIAN, ALLOTTEE OR TRUST NAME
3. ADDRESS OF OPERATOR POB 1757, Roswell, New Mexico 88201	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 766' FSL & 554 FWL of Section	8. FARM OR LEASE NAME Trinity
14. PERMIT NO.	9. WELL NO. A
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3827 GR	10. FIELD, AREA, TOL, OR WELL NAME Wildcat
	11. SEC. T. R. M. OR B.L. & S. SURVEY OR AREA Sec 28, T25, R38E
	12. COUNTY OR PARISH Lea
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data


NOTICE OF INTENTION TO:		SUBSEQUENT REPORT	
TEST WATER SHUT-OFF	<input type="checkbox"/>	WATER SHUT-OFF	<input checked="" type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	FRACTURE TREATMENT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	SHOOTING OR ACIDIZING	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	(Other)	<input type="checkbox"/>
(Other)	<input type="checkbox"/>	(NOTE: Report results of multiple completion on well completion or recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all marked and pertinent to this work.)*

Work performed 3/28/75: Ran 2106.03' of 8-5/8" 32# K-55 ST&C csg. & 2438.84' of 8-5/8" 24# K-55 ST&C csg. Set @ 4530 and cemented with 300 sks. 0/50 poz plus 200 sks. Neat. WOC 18 hrs. Tested to 1000 psi for 30 minutes. Held ok. Installed blow-out preventor and continued drilling operations.

18. I hereby certify that the foregoing is true and correct

SIGNED



TITLE

OPERATOR

DATE

5/9/75

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

MAY 13 1975

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

RECEIVED

1951

RECORDS SECTION