

NO. OF COPIES RECEIVED	
DISTRIBUTION	
ALANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
		5. State Oil & Gas Lease No. LG-1908
1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Drilling		7. Unit Agreement Name
2. Name of Operator Coquina Oil Corporation		8. Farm or Lease Name State G-B
3. Address of Operator P. O. Drawer 2960 Midland, TX 79701		9. Well No. 1
4. Location of Well UNIT LETTER A , 710 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 3 TOWNSHIP 14-S RANGE 32-E NMPM.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4316 GL		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Drilling to completion	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded @ 8:30 AM October 8, 1975. Oct. 9, drld 17 1/2" hole to 405'. Ran 14 jts 13 3/8" 68# K-55 8rd STC Youngstown steel casing landed @ 403.55', Cemented casing w/300 sx Howco Class C, 4% gel, followed by 125 sxs Class C, 2% CaCl₂. Displaced plug w/57 BFW. Left 30' of cement in casing. Plug down @ 2:24 AM, 10-9-75. Circ 75 sxs. Oct. 14, drlg ahead w/11" hole @ 3993' - no problems.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u><i>Alan Bump</i></u>	TITLE <u>Engineer Assistant</u>	DATE <u>10-15-75</u>
APPROVED BY _____	TITLE _____	DATE _____

CONDITIONS OF APPROVAL, IF ANY: