

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

-Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-6877

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry hole	7. Unit Agreement Name East Tatum State
2. Name of Operator Adobe Oil & Gas Corporation	8. Farm or Lease Name East Tatum State Unit
3. Address of Operator 1100 Western United Life Bldg., Midland, TX 79701	9. Well No. 1
4. Location of Well UNIT LETTER A 660 FEET FROM THE north LINE AND 990 FEET FROM THE east LINE, SECTION 35 TOWNSHIP 12-S RANGE 36-E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3967 Gr	12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plugged & abandoned as follows:

- Set CIBP @ 12,880' w/3 sx cement on top of plug.
- Circ hole w/9.5#/gal mud laden fluid.
- Cut off 5-1/2" csg @ 8543' & POH.
- Ran tbg 50' inside 5-1/2" stub & spotted 45 sx cement plug.
- WOC & tagged w/tbg.
- Spotted plugs @ following intervals:
6000-6100' (45 sx)
4650-4550' (50 sx) WOC & tagged.
2280-2180' (50 sx)
488-388' (50 sx)
20 to surface (10 sx)
- Cut off wellhead below ground level & installed dry hole marker
(Mud between plugs 9.5#)

Casing left in hole:

13-3/8" surface to 435'
8-5/8" surface to 4600' 5-1/2" 8492-13,294'

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bill Owens TITLE Engineer DATE 9/13/79

APPROVED BY A. H. Statten TITLE OIL & GAS INSPECTOR DATE JUN 20 1980

CONDITIONS OF APPROVAL, IF ANY: