

LEA
ADOBE OIL & GAS CORP. Austin
1 Hannah
Sec 17, T14S, R36E

NM
Page #2

3-12-79 Continued
Perf (Mississippian) 13,603-606' w/1 SPF
Acid (13,603-606') 2000 gals (15%)
Flwd est. 500 MCFGPD thru 3/4" chk
(13,603-606')
3-19-79 TD 13,832'; PBD 13,520'; Tstg
Acid (13,603-606') 1000 gals %20%)
Swbd 120 BLW (13,603-606')
Sqzd 13,603-606' w/50 sx
PB to 13,520'
Perf (Mississippian) 13,397-460' w/12 shots
(overall)
Acid (13,397-460') 4000 gals (20%)
Flwd 2700 MCFGPD in 4 hrs thru 19/64" chk,
TP 1400# (13,397-460') 4-4-22 NM

3-26-79 TD 13,832'; PBD 13,520'; Prep 4 Pts.
3-30-79 TD 13,832'; PBD 13,520'; WOSP
CAOF 7176 MCFGPD (13,397-460')
4-23-79 TD 13,832'; PBD 13,520'; Complete
(Mississippian) FOUR POINT GAUGES:
Flwd 810 MCFGPD, 8/64" chk, 60 mins, TP 2375#
Flwd 1480 MCFGPD, 12/64" chk, 60 mins, TP 2330#
Flwd 2685 MCFGPD, 16/64" chk, 60 mins, TP 2225#
Flwd 3347 MCFGPD, 18/64" chk, 60 mins, TP 1980#
LOG TOPS: Rustler 2200', San Andres 4600', Tubb
7478', Abo 8567', Wolfcamp 9798', Pennsylvanian
10,706', Canyon 11,051', Atoka 12,306',
Mississippian 13,220'
LOGS RUN: CNDL, DILL, DIPM
Rig Released 2-23-79
4-28-79 COMPLETION ISSUED

4-4-22 NM
IC 30-025-70392-78