

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Durham, Inc.		8. Farm or Lease Name Elkan
3. Address of Operator 219 S. Colorado, Midland, Texas 79701		9. Well No. 1
4. Location of Well UNIT LETTER <u>F</u> <u>2100</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>34</u> TOWNSHIP <u>14-S</u> RANGE <u>34-E</u> NMPM.		10. Field and Pool, or Wildcat Cerca (Penn)
15. Elevation (Show whether DF, RT, GR, etc.) 4131' G, 4146' KB		12. County

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK	<input type="checkbox"/>
TEMPORARILY ABANDON	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

PLUG AND ABANDON	<input type="checkbox"/>
CHANGE PLANS	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
COMMENCE DRILLING OPNS.	<input checked="" type="checkbox"/>	PLUG AND ABANDONMENT	<input type="checkbox"/>
CASING TEST AND CEMENT JOBS	<input checked="" type="checkbox"/>	OTHER	<input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Spudded at 10:30 a.m. MST, 4-28-79.
- Drilled 17½" hole to 406'. Ran 10 jts 13 3/8" 48#, H-40, smls casing, set at 400'. Cemented with 425 sx Class C + 2% CaCl, had full returns throughout but cement did not circulate. WOC 7 hrs. Ran temperature survey, cement 90' from surface. Cemented top 90' with an additional 100 sx Class C + 2% CaCl. Cement circulated. WOC 16 hrs, 4-30-79.
- Drilled 11" hole to 4405'. Ran 11½ jts 8 5/8" 24 & 32#, K-55, ST&C, smls casing, set at 4405'. Cemented with 1530 sx HLC + 15½ #/sx salt + 3#/sx Gilsonite + ½#/sx Floseal followed by 200 sx Class C + 2% CaCl. Cement did not circulate. Ran temperature survey, cement 135' from surface. WOC 12 hrs, 5-4-79.
- Drilling 7 7/8" hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Les Skinner TITLE Engineer DATE 5-9-79

APPROVED BY John Runyan
CONDITIONS OF APPROVAL, IF ANY

TITLE

MAY 15 1979