

NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - FORM C-101 FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
207 South 4th Street - Artesia, New Mexico 88210

4. Location of Well
UNIT LETTER G 1980 FEET FROM THE North LINE AND 1980 FEET FROM
THE East LINE, SECTION 18 TOWNSHIP 14S RANGE 36E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
3975.8'

5a. Indicate Type of Lease
State ☐ Fed ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name

8. Farm or Lease Name
Barbee "LL"

9. Well No.
1 1

10. Field and Pool, or Wildcat
Austin Miss.

12. County
Brewer

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ☐ ALTERING CASING ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐ OTHER ☐ CASING TEST AND CEMENT JOB ☒

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 387' - Spudded a 17½" hole at 10:00 AM 9-1-79. Ran 9 joints of 13-3/8" 64# H-40 (392') of casing set at 387'. 1-Insert Float at 347'. Cemented w/400. sacks of Class C 4% CaCl. Cement circulated 40 sacks to surface. PD 9:30 PM 9-1-79. WOC 12 hours, NU, cut off casing reduced hole to 12¼", drilled plug and tested to 600#. OK and resumed drilling.

TD 4650' - Ran 4675' of 8-5/8" casing set at 4650' as follows: 65 joints of 32# K-55 (2365'); 49 joints 24# K-55 (2310') (Total 4675'). 1-Guide shoe at 4650' and Diff-Fill Collar at 4610'. Cemented w/2200 sacks Howco Lite, 5#/sack gilsonite, 1/4# flocele/sack, tailed in w/150 sacks Class C 2% CaCl. PD 10:45 PM 9-9-79. WOC 6 hours and ran Temperature Survey, found top of cement at 1550'. WOC 18 hours, NU, and tested BOP' to 1500#. OK. Reduced hole to 7-7/8", drilled plug and tested to 600#. OK. Resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Ambrose

TITLE Geol. Secty.

DATE 9-22-79

Orig. Signed By
Jerry Sexton

SEP 26 1979

DATE