

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.D.S.	
LAND OFFICE	
OPERATION	

C.O. CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State ☒ For ☐
5. State Oil & Gas Lease No.
LG - 5419

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Name East Hightower
2. Name of Operator Harper Oil Company	8. Farm or Lease Name Frier
3. Address of Operator 904 Hightower Building Oklahoma City, Oklahoma 73102	9. Well No. 1
4. Location of Well UNIT LETTER L 660 FEET FROM THE West LINE AND 1980 FEET FROM THE South LINE, SECTION 29 TOWNSHIP 12S RANGE 34E N.M.M.	10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 4194.1 G.L.	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPS. ☐	PLUG AND ABANDONMENT ☐
FULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work; SEE RULE 1103.

1. Drilled to T.D. of 10,409' at 11:45 AM 2/6/80. Ran Open Hole Logs to 10,396'.
2. Ran 5½" casing as follows: 66 jts. 5½" 17# N-80 8rd LT&C (2724.40'), 92 jts. 5½" 17# K-55 8rd LT&C (3926.40'), 90 jts. 5½" 17# N-80 8rd LT&C (3750.54'), Halco float collar (1.45'), 1 jt. 5½" 17# N-80 8rd LT&C (41.72'), Halco float shoe (1.60') Total 249 jts. (10,446.21') Set at 10,407' KB. Cemented w/300 sacks 50-50 pozmix w/2% gel, 6#/sk salt, 0.5% Halad 22-A, followed w/275 sacks Class H w/0.5% Halad 22-A and 5#/sk KCL. Displaced at 1900# pressure. Plug down at 8:55 PM 2/10/80. Pressure to 2700#, float held okay.
3. Ran Temperature Survey to 10,362', top of cement at 8050' G.L.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Petroleum Engineer DATE 2/19/80

APPROVED BY [Signature] TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

FEB 22 1980