

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State ☒	Free ☐
5. State Oil & Gas Lease No.	
E-7555	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. Unit Agreement Name	
Name of Operator		8. Farm or Lease Name	
Rapid Company, Inc.		McKay State	
Address of Operator		9. Well No.	
c/o Oil Reports & Gas Services, Inc., Box 763, Hobbs NM 88240		2	
Location of well		10. Field and Fm., or Wildcat	
UNIT LETTER 0 660 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 18 TOWNSHIP 13S RANGE 32E NMPM.		Caprock Queen	
15. Elevation (Show whether DF, RT, GR, etc.)		12. County	
4362.6 GL		Lea	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
WELL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1123.

Moved out cable tools 3/6/80 at 1200', moved in rotary. Drilled 6/18" hole to 1600'. Lost 3 cones in hole, unable to recover. Hole caving. Ran 4 1/2" 9.5# J-55 casing to 1600 and cemented with 125 sacks Class C cement. Plug down 3:30 PM 7/16/80. Cement circulated. WOC 24 hours, drilled plug with 3 3/4" bit.

Ran 2 7/8" EUE tubing to 3077 and cemented with 150 sacks Class "C" cement. Cement circulated. Bumped plug 10:30 AM 7/19/80 with 1600#. WOC 24 hours, tested tubing with 1500# for 30 minutes, test OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed by John Runyan TITLE Agent DATE 8/18/80

APPROVED BY Geologist TITLE Geologist DATE AUG 19 1980

CONDITIONS OF APPROVAL, IF ANY:

(35 gals min)
Inject Pump cement down 2 1/8" - Flush to 250' if OK.

Pull on 2 1/2" to see if any free tubing.

Cut + Pull Out least 250' = tubing - (or Perf. 2 1/2" at 250')

Grill 4 1/2" to Surface w/ cement. (with or without grouting)

Install chg hole markers. Clean Location
Close all pits
