

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ ☐

5. State Oil & Gas Lease No.
LG-5680

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator
Yates Petroleum Corporation

Address of Operator
207 South 4th St., Artesia, NM 88210

Location of Well
UNIT LETTER F 1980 North 1980
LINE AND FEET FROM
THE West LINE, SECTION 18 TOWNSHIP 13S RANGE 33E N.M.P.M.

7. Unit Agreement Name

8. Farm or Lease Name
Bass ON State

9. Well No.
2

10. Field and Pool, or Wildcat
Baum-Upper Penn

15. Elevation (Show whether DF, RT, GR, etc.)
4290' GR

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

ENFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
ULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any prop-
work) SEE RULE 1103.

Spudded a 17-1/2" hole at 1:15 AM 12-18-80.

TD 410' Ran 11 joints of 13-3/8" 48# K-55 ST&C casing set at 410'. 1-Texas Pattern guide shoe at 410'. Insert float at 370'. Cemented w/400 sacks Class C 4% CaCl. Slurry weight 14.8, 1.32 cu ft/sack. PD 3:00 PM 12-18-80. Cement circulated 50 sacks. WOC 12 hours. Compressive strength at 70 degrees 1023 psi in 12 hours. Backed off and reduced hole to 12-1/4".

TD 4167' Ran 102 joints of 8-5/8" 24# & 32# K-55 ST&C casing as follows: 42 joints of 8-5/8" 32# K-55 ST&C, 58 joints of 8-5/8" 24# K-55 ST&C, 2 joints of 8-5/8" 32# K-55 ST&C casing set at 4167'. 1-Regular pattern guide shoe at 4167'. Insert float at 4122'. Cemented w/2317 sacks 65-35 Poz, 5#/sack Kolite, 1/4# celloflakes and 3% CaCl. Tailed in w/150 sacks Class C 2% CaCl. PD 11:30 PM 12-26-80. Bumped plug to 2150#, released pressure and float held okay. Circulated 150 sacks to pit. WOC 20 hours. Nippled up and tested to 1500#, OK. Reduced hole to 7-7/8".

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Orig. Signed by

Jerry Sexton

TITLE Engineering Secretary

DATE Jan. 6, 1981

Dist. L. Sexton

TITLE

DATE JAN 9 1981

CONDITIONS OF APPROVAL, IF ANY: