

MEASURED DEPTH FEET	DRIFT ANGLE D M	DRIFT DIRECTION D	COURSE LENGTH FEET	TRUE VERTICAL DEPTH FEET	R E C T A N G U L A R C O O R D I N A T E S FEET	DOGLEG SEVERITY DG/100FT
4200.	0 0	0	0.	4200.00	0.00	0.00
4300.	2 0	S 48 W	100.	4299.98	1.17 S	2.00
4400.	1 45	S 50 W	100.	4399.93	3.32 S	0.26
4500.	1 45	S 52 W	100.	4499.88	5.24 S	0.06
4600.	1 45	S 47 W	100.	4599.83	7.22 S	0.15
4700.	1 45	S 46 W	100.	4699.79	9.32 S	0.03
4800.	1 45	S 35 W	100.	4799.74	11.64 S	0.34
4900.	1 45	S 42 W	100.	4899.69	14.03 S	0.21
5000.	1 45	S 31 W	100.	4999.65	16.48 S	0.34
5100.	1 45	S 34 W	100.	5099.60	19.06 S	0.09
5200.	2 0	S 35 W	100.	5199.55	21.75 S	0.25
5300.	2 30	S 22 W	100.	5299.47	25.20 S	0.71
5400.	2 45	S 18 W	100.	5399.36	29.50 S	0.31
5500.	2 30	S 16 W	100.	5499.26	33.88 S	0.27
5600.	2 30	S 17 W	100.	5599.16	38.06 S	0.04
5700.	2 30	S 7 W	100.	5699.07	42.33 S	0.44
5800.	2 0	S 16 W	100.	5798.99	46.17 S	0.61
5900.	1 45	S 14 W	100.	5898.94	49.33 S	0.26
6000.	1 45	S 12 W	100.	5998.89	52.31 S	0.06
6100.	1 30	S 1 W	100.	6098.85	55.12 S	0.40
6200.	0 45	S 9 W	100.	6198.83	57.07 S	0.76
6300.	1 15	S 10 E	100.	6298.82	58.81 S	0.59
6400.	1 0	S 21 E	100.	6398.80	60.70 S	0.33
6500.	1 15	S 25 E	100.	6498.78	62.51 S	0.26
6600.	1 15	S 29 E	100.	6598.75	64.45 S	0.09
6700.	0 45	S 48 E	100.	6698.74	65.81 S	0.59
6800.	0 45	S 50 E	100.	6798.73	66.67 S	0.03
6900.	0 45	S 49 E	100.	6898.72	67.52 S	0.01
7000.	1 0	S 60 E	100.	6998.71	68.40 S	0.30
7100.	0 45	S 50 E	100.	7098.70	69.28 S	0.29
					26.22 W	
					25.23 W	
					24.23 W	
					22.99 W	
					21.74 W	