



	O. D.	I. D.	LENGTH	DEPTH
Drill Pipe or Tubing				
Drill Collars	5.75"	3"	1'	9789'
Reversing Sub				
Water Cushion Valve	4.50"	3.826"	9178'	
Drill Pipe	6 1/4"	2.25"	701'	
Drill Collars				
Handling Sub & Choke Assembly	5.75"	2.25"	1'	9879'
Dual CIP Valve - X over				
Dual CIP Sampler	5"	.75"	5'	9860'
Hydro-Spring Tester				
	5"	.75"	4'	
Multiple CIP Sampler				
	5"	.87"	10' (2 ea.)	
Extension Joint				
	5"	3.25"	5'	9879'
AP Running Case				
	5"	1.75"	5'	
Hydraulic Jar				
	5"	1"	3'	
VR Safety Joint				
Pressure Equalizing Crossover				
	7"	1.63"	5'	9892'
Packer Assembly				
	5"	1.68"	2'	
Distributor				
	7"	1.63"	5'	9897'
Packer Assembly				
Flush Joint Anchor				
Pressure Equalizing Tube				
Blanked-Off B.T. Running Case				
Drill Collars				
Anchor Pipe Safety Joint				
Packer Assembly				
Distributor				
Packer Assembly				
Anchor Pipe Safety Joint				
Side Wall Anchor				
Drill Collars				
	5.75"	3.50"	35'	
Flush Joint Anchor				
	5.75"	3.50"	5'	9935'
Blanked-Off B.T. Running Case				
				9940'
Total Depth				