

| Tool Description            | O.D.   | I.D.   | Length | Depth  |
|-----------------------------|--------|--------|--------|--------|
| DRILL PIPE                  | 4.5"   | 3.826" | 9644'  |        |
| DRILL COLLARS               | 6.5"   | 2.25"  | 598'   |        |
| REVERSING SUB               | 5.75"  | 2.625" | 1'     | 10242' |
| DRILL COLLARS               | 6.5"   | 2.25"  | 120'   |        |
| X/O                         | 6"     | 2.25"  | 1'     |        |
| HYDROSPRING TESTER MCIP     | 5"     | .75"   | 9'     | 10372' |
| EX-JOINT                    | 5"     | .87"   | 5'     |        |
| EX-JOINT                    | 5"     | .87"   | 5'     |        |
| AP RUNNING CASE             | 5"     | 3.25"  | 4'     | 10383' |
| JARS                        | 5"     | 1.75"  | 5'     |        |
| VR SAFETY JOINT             | 5"     | 1"     | 3'     |        |
| PACKER                      | 6.75"  | 1.53"  | 5'     | 10398' |
| DISTRIBUTOR VALVE           | 5"     | 1.68"  | 2'     |        |
| PACKER                      | 6.75"  | 1.53"  | 5'     | 10405' |
| ANCHOR PIPE SAFETY JOINT    | 5.75"  | 1.50"  | 4'     |        |
| X/O                         | 5.75"  | 2.375" | 1'     |        |
| DRILL COLLAR                | 6.50"  | 2.25"  | 30'    |        |
| X/O                         | 5.875" | 2.375" | 1'     |        |
| PERFORATED TAIL PIPE        | 5.75"  | 3.50"  | 17'    |        |
| BLANKED OFF BT RUNNING CASE | 5.75"  | 3.50"  | 4'     | 10460' |
| TOTAL DEPTH                 |        |        |        | 10464' |