

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State ☒ For ☐
5. State Oil & Gas Lease No.
L-7036

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator MWJ PRODUCING COMPANY	8. Farm or Lease Name Baum 18 State
3. Address of Operator 1804 First National Bank Bldg Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>A</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>18</u> TOWNSHIP <u>14S</u> RANGE <u>33E</u> N.M.P.M.	10. Field and Pool, or Wildcat Baum Upper Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4256' GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Casing Record: 13-3/8" at 418' (circulated cement)
8-5/8" at 4104' (circulated cement)
5-1/2" at 10150' (top of cement @ 8960')
Perforations from 9906' to 9920'

Proposed Plugging Procedure: 1) CIBP & 35' of cement on top at 9800'
(per Jerry Sexton 10/24/86) 2) 100' cement from 9000' to 9100'
3) 100' cement from 5400' to 5500'
4) 100' cement from 4050' to 4150' (tag)
5) 100' cement from 1600' to 1700'
6) 10 sx at surface and install dry hole marker
Mud between plugs (25# saltgel per bbl wtr)
estimated casing recovery 6000' of 5-1/2"

ORIGINAL MUST BE RETURNED TO THE DIVISION OF OPERATIONS FOR THE OCS APPROVED

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Pat Drexler TITLE Pat Drexler - Agent DATE 12/2/86

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR

APPROVED BY _____ TITLE _____ DATE DEC 4 1986

CONDITIONS OF APPROVAL, IF ANY: