STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

DISTRIBUTION		
SANTA PE		
FILE		
U.S.O.B.	_	
LAND OFFICE	i	
OFFRATOR		Ì

UIL CONSERVATION DIVISION

Form C-103

SANTA FE, NEW MEXICO 87501	
	Sa. Indicate Type of Leise
TILE TO THE TOTAL	tate X Fee
LAND OFFICE	
OPERATOR .	5. Sinte (ii) & Gas Lease No.
	LG 814
CHADDA MOTICES AND DEDODTS ON WELLS	
SUNDRY NOTICES AND REPORTS ON WELLS TO MAKE THIS FORM FOR PROPOSALS TO PRILL ON TO GEEPEN ON PLUG BACK TO A DIFFERENT MESERVOIR TO MAKE THIS FORM FOR PROPOSALS TO PRILL ON TO GEEPEN ON PLUG BACK TO A DIFFERENT MESERVOIR TO MAKE THIS SECRETARY FOR PROPOSALS.)	
USE "APPLICATION FOR PERMIT -" FERMI C-FUTFFOR SUCK VIOLOSE	7, Unit Agreement Name
OIL V CAR	
WELL X WELL OTHER.	8. Farm or Lease frame
ame of Operator	Woodpecker SY State
Yates Petroleum Corporation	9. Well No.
ddress of Operator	1
207 South 4th St., Artesia, NM 88210	
ocation of Well	10. Field and Fool, or Wildcat
A 660 FEET FROM THE NORTH LINE AND 660	Wildcat Permo Penn
UNIT LETTER A , OOO FEET FROM THE LINE AND OOO	
21 1/49 33E	NMPM.
THE East LINE, SECTION 21 TOWNSHIP 14S RANGE 33E	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
4211.2' GR	Lea
	177777777
Check Appropriate Box To Indicate Nature of Notice, Repo	ort or Other Data
NOTICE OF INTENTION TO:	SEQUENT REPORT OF:
NOTICE OF THE PARTY OF THE PART	
PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
SOUNTENEE OR ILLING OPHS.	PLUG AND ABANDONMENT
MPGRARILY ABANDON	
CHANGE PLANS CASING TEST AND CEMENT JO	Casing, Perforate, Treat X
OTHER 12040020	
OTHER	
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates	s, including estimated date of starting any propose
Describe Proposed or Completed Operations (Circuity state are persistent details) and proposed or Completed Operations (Circuity State are persistent details).	
7 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1	F 1/01/ 174 V FF and 20 defente
TD 10170'. Ran 43 joints 4-1/2" 17# LT&C N-80 and 196 joints 5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20 27, 28, 31 and 32'. Acidized well w/2500 gallons 7½% acid and	Ourton guide shoe set 10170. O Poz "H" and .5% CF-2, 1/4# O CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated O, 21, 22, 23, 24, 25, 26,
5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20	Ourton guide shoe set 10170. O Poz "H" and .5% CF-2, 1/4# O CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated O, 21, 22, 23, 24, 25, 26,
5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20	Ourton guide shoe set 10170. O Poz "H" and .5% CF-2, 1/4# O CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated O, 21, 22, 23, 24, 25, 26,
5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20	Ourton guide shoe set 10170. O Poz "H" and .5% CF-2, 1/4# O CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated O, 21, 22, 23, 24, 25, 26,
5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20	Ourton guide shoe set 10170. O Poz "H" and .5% CF-2, 1/4# O CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated O, 21, 22, 23, 24, 25, 26,
5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20	Ourton guide shoe set 10170. O Poz "H" and .5% CF-2, 1/4# O CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated O, 21, 22, 23, 24, 25, 26,
5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20	Ourton guide shoe set 10170. O Poz "H" and .5% CF-2, 1/4# O CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated O, 21, 22, 23, 24, 25, 26,
5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20	Ourton guide shoe set 10170. O Poz "H" and .5% CF-2, 1/4# O CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated O, 21, 22, 23, 24, 25, 26,
5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20	Ourton guide shoe set 10170. O Poz "H" and .5% CF-2, 1/4# O CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated O, 21, 22, 23, 24, 25, 26,
5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20	Ourton guide shoe set 10170. O Poz "H" and .5% CF-2, 1/4# O CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated O, 21, 22, 23, 24, 25, 26,
5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20	Ourton guide shoe set 10170. O Poz "H" and .5% CF-2, 1/4# O CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated O, 21, 22, 23, 24, 25, 26,
5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20	Ourton guide shoe set 10170. O Poz "H" and .5% CF-2, 1/4# O CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated O, 21, 22, 23, 24, 25, 26,
5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20 27, 28, 31 and 32'. Acidized well w/2500 gallons 7½% acid and	Poz "H" and .5% CF-2, 1/4# % CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated D, 21, 22, 23, 24, 25, 26, H 10 balls.
5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20 27, 28, 31 and 32'. Acidized well w/2500 gallons 7½% acid and	Poz "H" and .5% CF-2, 1/4# % CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated D, 21, 22, 23, 24, 25, 26, H 10 balls.
5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20, 27, 28, 31 and 32'. Acidized well w/2500 gallons 7½% acid and .50 acid and .50 acid well w/2500 gallons 7½% acid and .50 acid acid well w/2500 gallons .50 acid and .50 acid acid well w/2500 gallons .50 acid acid acid .50 acid acid acid well w/2500 gallons .50 acid acid .50 acid acid .50 acid .	Poz "H" and .5% CF-2, 1/4# 66 CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated 0, 21, 22, 23, 24, 25, 26, 10 balls.
5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20, 27, 28, 31 and 32'. Acidized well w/2500 gallons 7½% acid and and the same same same same same same same sam	Poz "H" and .5% CF-2, 1/4# 66 CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated 0, 21, 22, 23, 24, 25, 26, 10 balls.
5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20 27, 28, 31 and 32'. Acidized well w/2500 gallons 7½% acid and	Poz "H" and .5% CF-2, 1/4# 66 CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated 0, 21, 22, 23, 24, 25, 26, 10 balls.
Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20, 27, 28, 31 and 32'. Acidized well w/2500 gallons 7½% acid and and salt and sa	Poz "H" and .5% CF-2, 1/4# CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated D, 21, 22, 23, 24, 25, 26, H 10 balls.
5-1/2" 17# N-80 (Total 10206') of casing set 10170'. 1-Hallib Auto fill float collar set 10125'. Cemented w/740 sacks 50/50 celloseal, 5#/sack salt. Tailed in w/200 sacks Class "H", .5% Bumped plug to 500 psi, released pressure and float held okay. 9905-32' w/16 .50" holes as follows: 9905, 06, 07, 08, 19, 20, 27, 28, 31 and 32'. Acidized well w/2500 gallons 7½% acid and and the same same same same same same same sam	Poz "H" and .5% CF-2, 1/4# CF-2. PD 7:15 PM 3-27-82. WOC. WIH and perforated D, 21, 22, 23, 24, 25, 26, H 10 balls.

, t

RECEIVED

APR 23 1502

C.C.S. HOBBS OFFICE

STATE OF NEW MEXICO . ENERGY AND MINERALS DEPARTMENT

	~~~	
NO. OF COPIES RECEIVED	1	
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		

## UIL CONSERVATION DIVISION

P. O. BOX 2088 SANTA FE, NEW MEXICO 87501

Form C-103			
(O) (III C-103	Farm	C-101	
Revised 10-1-	Revis	cad 10-1	_

rice	Sa. Indicate Type of Lease
U.S.G.S.	State X Fee
OPERATOR	5, State Oil & Gas Lease No. LG 814
SUNDRY NOTICES AND REPORTS ON WELLS	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL ON TO OFFPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  USE "APPLICATION FOR PERMIT —" IFORM C-101) FOR SUCH PROPOSALS.)	7, Unit Agreement Name
OIL X GAB OTHER-	8. Farm or Lease Name
2. Name of Operator	Woodpecker SY State
Yates Petroleum Corporation	9. Well No.
207 South 4th St., Artesia, NM 88210	10. Field and Pool, or Whicat
4. Location of Well  UNIT LITTER A 660 FEET FROM THE NORTH LINE AND 660 FEET FROM	UNDESIGNATED
THE East LINE, SECTION 21 TOWNSHIP 148 NAME 33E NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.) 4211.2 GR	12. County Lea
Check Appropriate Box To Indicate Nature of Notice, Report or Oth	per Data
NOTICE OF INTENTION TO: SUBSEQUENT	REPORT OF:
PERFORM REMEDIAL WORK	ALTERING CASING
TEMPORARILY AGANDON COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CABING CHANGE PLANS CASING YEST AND CEMENT JGB	Γ
GTHER	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1703.	estimated date of starting any propose
Set 40' of 20" conductor pipe. Spudded a 17-1/2" hole at 2:30 AM 2-11-13-3/8" 48# casing set at 445'. Texas Pattern guide shoe at 445'. Insert Cemented w/450 sacks Class "C" 2% CaCl2. PD 5:00 PM 2-11-82. Bumped pressure and float held okay. Cement circulated 45 sacks to surface. 11:00 AM 2-12-82. WOC 18 hours. Reduced hole to 12-1/4". Drilled plu Ran 100 joints 8-5/8" 32# K-55 ST&C of casing set at 4200'. 1-Texas pattern at 4200'. Insert float 4158'. Cemented w/2000 sacks 50/50 Poz mix. To Class "C" with .5% CFR-2. PD 6:15 PM 2-22-82. Cement circulated 35 sacks to pit. WOC. 2-23-82. WOC 12 hours. Nippled up and tested to 1000 psi, okay. Reduce Drilled plug and resumed drilling.	of the float at 403'.  Foliage to 550 psi, released WOC. Drilled out at all and resumed drilling. Attern guide shoe set alled in w/300 sacks acks to pit. WOC.  Drilled out 6:15 AM
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.  2. So aller Tires Engineering Secretary  ORIGINAL SIGNED BY	DATE 2-25-82
JERRY SEXTON	MAR 1 1982
APPROVED BY DISTRICT   SUPR	DATE THE LIVE
CONDITIONS OF APPROVAL, IF ANY	

RECEIVED

MAR 01 1982

HOBBS COTTO