

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
K-4177	

SUNDARY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG SALS TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FC-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Southland Royalty Company		8. Farm or Lease Name Baum State
3. Address of Operator c/o Oil Reports & Gas Services, Inc. Box 763, Hobbs, NM 88240		9. Well No. 1
4. Location of Well UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 8 TOWNSHIP 14S RANGE 33E NMPM.		10. Field and Pool, or Wildcat Baum Upper Penn
15. Elevation (Show whether DF, RT, GR, etc.) 4245.1 GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled out surface plug 4/7/82. Drilled plugs and circulated hole clean to 10,050. Cemented 5½" 17.20# N-80 casing at 10,050 with 1750 sacks Halliburton Lite & 525 sacks 50/50 Pozmix. Plug down 4:35 PM 7/10/82. Ran temperature survey, found top of cement at 7008.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u><i>Ronnie Haller</i></u>	TITLE <u>Agent</u>	DATE <u>7/15/82</u>
ORIGINAL SIGNED BY		
APPROVED BY <u>JERRY SEXTON</u>	TITLE <u></u>	DATE <u>JUL 16 1982</u>
CONDITIONS OF APPROVAL, IF ANY		