

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name	
M.F. Walker	
9. Well No.	
1	
10. Field and Pool, or Wildcat	
S.W. Gladiola	
12. County	
Lea	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	
2. Name of Operator	
Eaton Industries of Houston, Inc.	
3. Address of Operator	
3104 Edloe, Ste. 200 Houston, TX 77027	
4. Location of Well	
UNIT LETTER <u>0</u> <u>1980</u> FEET FROM THE <u>East</u> LINE AND <u>660</u> FEET FROM	
THE <u>South</u> LINE, SECTION <u>27</u> TOWNSHIP <u>12</u> RANGE <u>37</u> N.M.P.M.	
15. Elevation (Show whether DF, RT, GR, etc.)	
3891.7	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 295 joints (12,226') 5-1/2" 17# S-95 N-80 & K-55. Cement with 520 sx Lite + 10 #/sk salt + .4% Hal 22-A followed by 200 sk "H" 50/50 Poz w/2% gel plus 2.5 #/sk KCL + .6% Hal 22-A. Displace with 289 bbls. Plug did not bump. (Conservation Commission was notified).

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mark S. Carr TITLE Drilling Consultant DATE 12-27-82
ORIGINAL SIGNED BY JERRY SEXTON DISTRICT 1 SUPR. DATE DEC 30 1982